COCATION OF WATER WELL:   Fraction   SE
istance and direction from nearest town or city street address of well if located within city?    WATER WELL OWNER:   Verlin Pfannenstiel
WATER WELL OWNER:   Verlin Pfannenstiel
WATER WELL OWNER: Verlin Pfannenstiel  R#, St. Address, Box # PO Box 39  Board of Agriculture, Division of Water Resource Application Number:
R#, St. Address, Box # PO Box 39
ty, State, ZIP Code
LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:  Depth(s) Groundwater Encountered 1 ft. 2 ft. 3  WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr  Pump test data: Well water was ft. after hours pumping gp  Bore Hole Diameter 6 in. to 52 ft. and in. to  WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  Velded  7 Fiberglass  Threaded Flush  In. to 49 ft., Dia in. to  Welded  7 Fiberglass  Threaded Flush  1 Steel 3 Stainless steel 5 Fiberglass  8 RMP (SR) 10 Asbestos-cement  1 Steel 3 Stainless steel 5 Fiberglass  8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  5 Gauzed wrapped 8 Saw cut 11 None (open hole)
Depth of Completed Well Statistics of the Section Box:    Depth of Completed Well Statistics of the Section Box:   Depth of Completed Well Statistics of the Section Box:   Depth of Completed Well water was   Section Box:   Depth of Complete Box:   Section Box:
WELL'S STATIC WATER LEVEL  Fit. below land surface measured on mo/day/yr  Pump test data: Well water was fit. after hours pumping gp  Est. Yield gpm: Well water was fit. after hours pumping gp  Bore Hole Diameter 6 in. to 52 fit. and in. to  WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample wa submitted  Water Well Disinfected? Yes No X  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  Pump test data: Well water was fit. after hours pumping gp  In in. to 49 fit. Dia in. to fit.
Pump test data: Well water was ft. after hours pumping gp  Est. Yield gpm: Well water was ft. after hours pumping gp  Bore Hole Diameter 6 in. to 52 ft. and in. to  WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X if yes, mo/day/yr sample was submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  Velded  Threaded Flush  In. to 49 ft., Dia in. to ft., Dia in. to  Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
Well water was ft. after hours pumping gp Bore Hole Diameter 6 in. to 52 ft. and in. to  Well WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted water well Disinfected? Yes No X  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  Velded  2 PVC 4 ABS 7 Fiberglass Threaded Flush  Claim keasing diameter 1 in. to 49 ft., Dia in. to ft., Dia in. to  Classing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  5 GREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
Bore Hole Diameter 6 in. to 52 ft. and in. to  WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  PURCL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below)  Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was water Well Disinfected? Yes No X  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  PURCL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below)  Water Well Disinfected? Yes No X  Welded CASING JOINTS: Glued Clamped  Clamped Flush  Threaded Flush  Casing height above land surface 0 in. to ft., Dia in. to  Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below)  S WELL WATER TO BE USED AS: 5 Public water supply 9 Dewatering 12 Other (Specify below)  S If yes, mo/day/yr sample was submitted to Department? Yes No X If yes, mo/day/yr sample was submitted water well Disinfected? Yes No X  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  2 PVC 4 ABS 7 Fiberglass Threaded Flush  Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted 1 Steel 3 RMP (SR) 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass Threaded Flush In. to 49 ft., Dia in. to ft., Dia in. to casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well  Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted water Well Disinfected? Yes No X  TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  2 PVC 4 ABS 7 Fiberglass Threaded Flush  Blank casing dlameter 1 in. to 49 ft., Dia in. to ft., Dia in. to casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted water Well Disinfected? Yes No X Submitted Casing Joints: Glued Clamped Submitted Casing Joints: Glued Submitted to Department? Yes No X Submitted to Department Yes No
TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  2 PVC 4 ABS 7 Fiberglass  Staink casing diameter 1 in. to 49 ft., Dia in. to ft., Dia in. to sasing height above land surface 0 in., weight 0.703   Ibs./ft. Wall thickness or gauge No.   SCH. 40    YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  5 Gauzed wrapped 8 Saw cut 11 None (open hole)
TYPE OF BLANK CASING USED:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  2 PVC 4 ABS 7 Fiberglass Threaded Flush  Casing diameter 1 in. to 49 ft., Dia in. to ft., Dia in. to sating height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Steel         3 RMP (SR)         6 Asbestos-Cement         9 Other (specify below)         Welded           2 PVC         4 ABS         7 Fiberglass         Threaded         Flush           Blank casing diameter         1 in. to         49 ft., Dia in. to         in. to         ft., Dia in. to           Blank casing height above land surface         0 in., weight         0.703         lbs./ft. Wall thickness or gauge No.         SCH. 40           YPE OF SCREEN OR PERFORATION MATERIAL:         7 PVC         10 Asbestos-cement           1 Steel         3 Stainless steel         5 Fiberglass         8 RMP (SR)         11 Other (specify)           2 Brass         4 Galvanized steel         6 Concrete tile         9 ABS         12 None used (open hole)           3 CREEN OR PERFORATION OPENINGS ARE:         5 Gauzed wrapped         8 Saw cut         11 None (open hole)
2 PVC 4 ABS 7 Fiberglass Threaded Flush  llank casing diameter 1 in. to 49 ft., Dia in. to 6  casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
Slank casing diameter 1 in. to 49 ft., Dia in. to ft., Dia in.
Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open noie)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open noie)  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 49 ft. to 51 ft. From ft. to
From ft. to ft. From ft. to
GRAVEL PACK INTERVALS: From 47 ft. to 52 ft. From ft. to
From ft. to ft. From ft. to
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals From 2 ft. to 47 ft. From ft. to ft. From ft. to
What is the nearest source of possible contamination:  10 Livestock pens  14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? How many feet?
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 0.5 Concrete Silty Clay, dark brown to brown, with
0.5 52 trace fine sand below 40'
0.00104/42
Survey report date: 06/21/13 Latitude: N 38.885972
Landue: N 33.33372
Longitude: W 99.3 10230
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and
completed on (mo/day/yr) 03/27/13 and this record is true to the best of my knowledge and belief. Kansa
Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 06/24/1
under the business name of GSI Engineering, LLC by (signature) (A) INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S
Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.