GSI Job No. 0	57335							. 2055	70	7	MW-7
4 II COATION OF	VATER WELL		ER WELL RECORD	Form WV		KSA 82a-1					
1 LOCATION OF V		1			}	n Number	1	ship Numb		Range Numb	_
County:	Saline	NW 1/4	SW ½	NW 1/4		31	<u></u>	13	S R	2	W
Distance and direction			ddress of well if loc	cated within	city?						
2250 N.			oo rooted								
2 WATER WELL O			corporated								
RR#, St. Address, B				- 040-4				_	ure, Division of	f Water Res	ources
City, State, ZIP Cod			Lake City, UT	84054			Applica	ation Numb	er:		
3 LOCATE WELL'S	ON BOX	H 4 DEPTH OF	COMPLETED WEI	1.1	32	ft FIF	/ΔΤΙΟΝ:		1217.27	TOC	
¥		Depth/s) Group	dwater Encountere	 .d 1		\\\	2		# 3		#
		WELL'S STATE	C WATER LEVEL	28.85	4 6	olow lond o	urface me	acured on	1t.	10-1-0	ft.) 5
xNW	NE	l									×
W W			np test data: Well								
÷ "		Est. Yield	gpm: Well	I water was		[†]	t. atter		hours pumpin	ıg	
sw	5	Bore Hole Diam	neter 8.5 in TO BE USED AS: iic 3 Feed lot	n. to	32		ft. and		in. to		ft.
Syv	- SE 1	1 Domest	ic 3 Feed lot	6 Oil field	water sup I water si	abih Shià	9 Dev	conoluonin vatering	g IIInje 12 Oth	cuon w e ll er (Specify I	below)
† <u>L</u> <u>i</u>		2 Irrigation	n 4 Industrial	7 10000	nd acedo	n (domosti	a) 10 M	noitoring w		or (opoon)	50.0,
	S										
		1	l/bacteriological sa	imple submit	ted to De						
E TYPE OF DIAM		submitted							Yes		
5 TYPE OF BLANK			5 Wrought Iro					NG JOINTS	6: Glued	Clampe	ed
1 Steel			6 Asbestos-C	ement 9	Other (s	specify belo	ow)		Welded		
2 PVC	4 AB		7 Fiberglass						Threaded		
Blank casing diamet	ter 2	in. to 2	2 ft., Dia		in. to		ft., Dia		in. to		ft.
Casing height above TYPE OF SCREEN	e land surface	Flushmount	in., weight	0.70	3	lbs./ft.	Wall thick	ness or ga	uge No.	Sch. 4	0
TYPE OF SCREEN	OR PERFORAT	ION MATERIAL:			7 F	PVC		IO Asbesto	os-cement		
1 Steel	3 Sta	inless steel	5 Fiberglass		8 F	RMP (SR)		11 Other (specify)		
2 Brass	4 Gal	vanized steel	5 Fiberglass6 Concrete til	ie	9 A	ABS `	1	2 None u	sed (open hol	e)	
SCREEN OR PERF	ORATION OPEN	INGS ARE:	5	Gauzed wra	apped				11 N		hole)
1 Continuous	slot	3 Mill slot	6	Wire wrapp	ed		9 Drille	d holes			
2 Louvered s	hutter	4 Key punched		Torch cut			10 Othe	r (specify)			
SCREEN-PERFOR	ATED INTERVAL	S: From	22 ft. to		32	ft. F	From		ft. to		ft.
		From	ft. to	,		ft. F	From		ft. to		ft.
GRAVEL PA	ACK INTERVALS				32	ft. I	From		ft. to		ft.
		From									,
6 GROUT MATER	IΔI· 1 No		2 Cement grout		3 Bent	nite	4 Other				
Grout Intervals F			π. From		nt. to	40 15	n.	From	π.	to	π.
What is the nearest	•		- 7.5	th makes					14 Abandor		ell
1 Septic tank 2 Sewer line		4 Lateral line: 5 Cess pool		it privy		11 Fuel	•		15 Oil well/		
3 Watertight	_			ewage lago	on		lizer storag		16 Other (s	pecity below	"
Direction from well?		6 Seepage pi	ii 9 F	eedyard			cticide stor	age			
FROM TO		LITHO	DLOGIC LOG		FROM	How many	y teet?	PLUG	GING INTER	VALS	
0 0.7		Asphalt	DEGGIO EGG		I COIVI	 		- FEGG	ONO INTER	VALO	
0.75 1.2		Fill, gravel					 				
1.25 13		Clay, stiff, bro	own								
13.5 32		Silt, stiff, brov									
							ļ				
							L				
7 CONTRACTOR	'S OR LANDOW	NER'S CERTIFICA	TION: This water	well was (1)	construc	ted, (2) rec	onstructed	or (3) plug	ged under my	jurisdicti d n	and was
completed on (mo/d	day/yr)	10	-1-05		and thi	s record is	tryle to the	best of my	knowledge a	nd belie K	ansas
Water Well Contrac			531						d on molday		

Geotechnical Services, Inc.