USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction SE _{1/4} SW _{1/4} NE _{1/4} | | Section number | | Township number | Range number | |
|---|--------|--|--|--------------------------------|---|---|-------------------------------|----------------------|
| 1. Location of well: | Saline | | | | | τ 13 s | R 2 E₩ | ŀ |
| | | | | ner of well: A. E. Rose (Rose) | | | | |
| New Cambria R.R. or streets Street address of well location if in city: City, state, z | | | | | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | 6. Bore hole dia. 8 in. Well depth 50 ft. | Completion date | |
| NE XI E | | | | | | 7 Cable tool X_ Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary 8. Use: X_Domestic Public supply Industry Irrigation Air conditioning Stock | | |
| SW SE 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | | | | | Lawn Oil field water Other 9. Casing: Material PISt Height: Above or telem Threoded Welded 9 Surface 18 in. RMP X PVC Weight Ibs./ft. Dia. 5 in. to 50 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 2.258 | | |
| 11 Mile | | | | | | | | |
| 5. Type and color of material | | | | From | То | 10. Screen: Manufacturer's name | | |
| Top soil | | | | 0 | 5 | Western Plastics Type | | |
| Clay | | | | 5 | 30 | | | |
| Sand | | | | 30 | 34 | | | |
| Clay | | | | 34 | 41 | | | |
| Gravel | | | | 41 | 50 | 12. Pumping level below land surfaces: | | |
| | | | | | | ft. after | nrs. pumpingg.p.m. | |
| | | | | | | Estimated maximum yield | g.p.m. mo./day/yr. | |
| | | | | | | Yes A No Date 14. Well head completion: Pitless adapter 18 inches above grade | | |
| | | | | ļ | | Pitless adapter 15. Well grouted? Yes | | ۱, |
| | | | | | | With: Neat cement Bentonite X Concrete Depth: From O ft. to 10 ft. | | |
| | | | | <u></u> | | 16. Negrest source of possible contamination: OLD ft. 50 Direction north TypeSewer | | |
| | | | | | | Well disinfected upon comple | tion? X Yes No | 10" |
| | | | | ļ | | Manufacturer's name Model number 9D9Po51 | Reda _ HP _ 1/2 _ Voits220 | للاا [" |
| | | | | | | Length of drop pipe 40 | ft. capacity 12 g.p.m. | (g) ~ |
| | | | | | | Type: X Submersible | Turbine | ا ا |
| (Use a secand sheet if needed) | | | | | | Jet Centrifugal | Reciprocating | * (v) * (r) |
| 18. Elevation: 19. Remarks: Concrete slab was poured | | | | | 20. Water well contractor's of This well was drilled under m | certification: y jurisdiction and this report | ر ا . لر ا | |
| Topography: Hill | | | | | is true to the best of my knowledge and belief. Rader Drilling Co. 194 Business name Address Carlton, Kansas 671,29 Signed Authorized representative | | | |
| Slope Upland Valley | | | | | | | | |
| | | | | | | <u> </u> | | 113 |