			WATER	WELL RECURD	Form v	/WC-5	KSA 82a-	1212				
1 LOCATION OF WATER WELL:			Fraction	C.D.	BTT.T	Section	on Number	Townsh	ip Number	Ra	nge Num	iber.
County: ELLIS			NW 1/4	SE 1/4	NW 1/4		8	Т	<u>13 s</u>	R	20_	_E(W )
Distance a	and direction	from nearest town of	or city street add	ress of well if loc	ated within	city?						$\sim$
2 WATER	R WELL OW	/NER: We]	ber Servi	ce & Rep	air							
RR#, St.	Address, Bo	×#: E1	lis, Ks.	67637				Board	of Agriculture,	Division o	f Water f	Resources
	, ZIP Code	:					MW#13		ation Number:			
3 LOCATI	E WELL'S L IN SECTIO	OCATION WITH 4 N BOX:										
	<u> </u>	De	ptn(s) Groundwa	ter Encountered	8 62		π. 2		π.	3		π.
	i	WE		ATER LEVEL								
-	NW	NF		est data: Well w								
Est. Yield gpm: Well water was										umping		gpm
									n. to		ft.	
[₹	!	!     WE	LL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
i	- SW	SE	1 Domestic	3 Feedlot					) 12			
	Î,	ī	2 Irrigation	4 Industrial		_	-		<u>well</u>			
L	1	<b>■</b> Wa	is a chemical/bac	cteriological samp	le submitte	d to Dep	artment? Ye	sNo	<b>.x</b> ; If ye	s, mo/day/y	r sample/	was sub-
<u> </u>		j mit	ted	<del></del>			Wat	er Well Disin	fected? Yes		No x	
5 TYPE C	OF BLANK (	CASING USED:	5	Wrought iron	8 (	Concrete	e tile	CASING	G JOINTS: Glu	ed	Clamped	1
1 Ste	eel	3 RMP (SR)	6	Asbestos-Ceme	nt 9 (	Other (s	pecify below	)	Wel	ded		
2 PV		4 ABS	7	Fiberglass					Thre	aded x		
Blank casi	ing diameter	and surface	to 1 7	ft., Dia		in. to .		ft., Dia		. in. to		ft.
Casing hei	ight above la	and surface	in	., weight	7.1	6	Ibs./fr	t. Wall thickn	ess or gauge	No • . !	54	
TYPE OF	SCREEN O	R PERFORATION M	IATERIAL:			7 PVC			Asbestos-cem			
1 Ste	eel	3 Stainless ste	el 5		8 RMP (SR)			11 Other (specify)				
2 Bra	ass	4 Galvanized	•			9 ABS			12 None used (open hole)			
SCREEN (	OR PERFO	RATION OPENINGS	ARE: 5 Gauzed v						11 None (open hole)			
1 Co	ontinuous slo	t 3 Mill si	lot		re wrapped			9 Drilled ho	oles		` '	,
2 Lo	uvered shut	ter 4 Key p	ounched	7 To	rch cut			10 Other (sr	pecify)			
SCREEN-	PERFORATI	ED INTERVALS:	From	17 ft. to		27	ft From	1	ft.	to		
				ft. to								
0	GRAVEL PA	CK INTERVALS:	From		)	27	ft From	1	ft.	to		
			From	ft. to			ft., From					ft.
6 GROUT	MATERIAL			Cement grout	3	Bentoni						
Grout Inter		m0			11,	£-510	רו		m			
	e nearest so	ource of possible	tamination:			(3)	10 Livesto					
1	eptic tank	4 Lateral li			11 Fuel storage			<ul><li>14 Abandoned water well</li><li>15 Oil well/Gas well</li></ul>				
2 Sewer lines 5 Cess poor				agoon	<u> </u>							
3 Watertight sewer lines 6 Seepage				-	13 Insecticide storage			16 Other (specify below) Removed Fuel Storage				
Direction f	_	or mics o occpage	pii	9 Feedyard			How man	_				
FROM	TO		LITHOLOGIC LO	G.	FRO	ом Т	TO	y leet?	PLUGGING	INTERVAL	S	
0	5	Topsoil				-						
5	10	Silt, ver	v fine sa	and, trac	е			·/				
		of clay		· · · · · · · · · · · · · · · · · · ·								
10_	15	Silt & ve	rv fine s	sand								
15	27	Med. to c	oarse Sai	nd/ a tra	ce			-				
		silt & cl										
		<u> </u>	<u> </u>									
										<del>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</del>		
	1					L	L					
7 CONTE	RACTOR'S	OR LANDOWNER'S	CERTIFICATION	I: This water well	l was (1) <u>co</u>	onstructe	<u>ed. (</u> 2) recor	structed, or	(3) plugged ur	ider my jur	isdiction	and was
completed	on (mo/day/	year) 3 – 25 – s License No	ン.4		• • • • • • •	a	nd this record	d is true to th	e best of my k	nowledge a	ınd belief	i. Kansas
under the I	business na	me of Woofte	r Pump &	werr, Tr	IC.		by (signatu	ıre)	and A	W.	1000	110