13

S

9

1 LOCATION OF WATER WELL:

Ellis

SE

1/4

SW

County:

ı		
1		
1		
1		
1		
1		
1	_	
ł	\mathbf{o}	
Ļ	Ŧ	
ı	#	
ı		
1	$\overline{}$	
ı	FCE	
ì	m	
ì	_	
Į	<u></u>	
ı	ഗ	
ı	m	
ı	***	
1	USE ONLY	
1	¥	
ŀ	Z	
ı	_	
ı	~	
ı	•	
l		
t		
Ł		
l		
í		
1		
ŀ		
l		
ı		
ı		
ŧ		
1		
ı		
l		
l		

20

R

2 WATER WELL OWNE	: Golden Belt C	oop					
RR#, St. Address, Box #	: Hwy 40 & Mor	roe			Board of Agric	culture, Division of W	ater Resources
ity, State, ZIP Code	: Ellis, Ks 6763				Application No	umber:	
LOCATE WELL'S LOC	ATON WITH 4	U OF COMPLETED WELL	22 8	A F1 F1/A	TION.		
AN "X" IN SECTION BO N	IX: DEPT	H OF COMPLETED WELL	22.0	π. ELEVA	HON:		
	Deptn(8)	Groundwater Encountered 1	7 20	π. Z	: 	π. 3	ft.
	WELLS	STATIC WATER LEVEL 1					
NW	NE	Pump test data: Well water					
w X	Est. Yield	gpm: Well water	was	ft. 8	ifter	hours pumping	gpm
┋┈┠╴ ╏╺╸┠╸	Bore Hole	Diameter 11 in. to	hlic water eur	ft.	and 8 Air condition	in. to	ft.
	1 D	omestic 3 Feed lot 6 Oil	field water su	pply	9 Dewatering	12 Other (Specify below)
Svv	2 lrr	rigation 4 Industrial 7 La	wn and garde	n (domestic)	10 Monitorin	g well	BVE
		emical/bacteriological sample si					r sample was
S	submitted					ed? Yes	No X
TYPE OF BLANK CAS		5 Wrought Iron	8 Concrete		······································	NTS: Glued	
1 Steel		6 Asbestos-Cement				Welded	
			•				E .
2 PVC	4 ABS	7 Fiberglass				Threaded	
slank casing diameter	in. to	12.8 ft., Dia in., weight 2	in. to		ft., Dia	in. to	ft.
Casing height above land FYPE OF SCREEN OR P	SUITACE U	in., weight	.0/1	lbs./ft. W	all thickness or	gauge No.	.23/
1 Steel	CHORATION MATERI	AL: 5 Fiberglass	[7]P	VC	10 Asb	estos-cement	
2 Brass	4 Galvanized steel	6 Concrete tile	0 4	MP (SK) BS	11 Oth	er (specify) e used (open hole)	
SCREEN OR PERFORAT			•			e used (open noie) 11 None	
1 Continuous slot	3 Mill slot	6 Wire v	rapped		9 Drilled holes		s (open noie)
2 Louvered shutter	4 Key punch	hed 7 Torch				; cify)	j
SCREEN-PERFORATED	INTERVALS: From	12.8 ft. to	22.8	ft. Fro	m	ft. to	ft.
	From	ft. to		ft. Fro	m	ft. to	ft.
GRAVEL PACK I	ITERVALS: From	ft. to 11.0 ft. to	22.8	ft. Fro	m	ft to	
•	From	ft. to		ft. Fro	m	ft. to	
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bento	nite 4	Other		
 Grout Intervals From	Q 2 ft. to 1	t. From	ft. to	,	ft. From	ft to	
What is the nearest source	of possible contaminal	tion:		10 Livestoo		14 Abandoned v	
1 Septic tank	4 Latera	al lines 7 Pit privy			rage	15 Oil well/ Gas	
2 Sewer lines	5 Cess		agoon		r storage		- F
3 Watertight sewer	ines 6 Seepa	age pit 9 Feedyard			ide storage		
Direction from well?				How many fe			
FROM TO			FROM	TO	PL	UGGING INTERVAL	S
0 20	CL, silty c	lay, low plastic w/					
20 22.8		to med sd					
20 22.0	Correction	graded sd, fine to trace fine to coarse	 				
	gravel	trace fine to coarse	 				
	N. a. A.		 				
							
			1				
					-CO	DDECT	
			 		<u> </u>	INLOI	
		· · · · · · · · · · · · · · · · · · ·	 				
7 CONTRACTOR'S OF	ANDOWNED'S CERTI	FICATION: This water well was	(1) constructs	1 (2)	whod e- /2\ -1-	mand under miles	atlan and
	ANTOWNIER O CERTI	1-17-07	() CONSTRUCTED	a, (∡) reconstr	ucteu, or (3) plu	yyea unaer my jurisa	cuon and was
completed on (mo/day/yr)	onno No	1-17-07 554	and this	recora is true	to the best of r	ny knowledge and be	Nansas
VOIGE (VAII (`AAAAAAA '							
Vater Well Contractor's Li Inder the business name	ense No.	Noofter Pump & Well II the correct answers. Send three co	Inis vva	er vveli Reco	ra was complet	red on (mo/day/yr)	02-02-07