				WELL RECOR) Form WWC-			IAIAIA	
	ON OF WATE		Fraction	NE	1 -	ection Number		I	Range Number
County:		llis	NW ½			9	<u> </u>	S	R 20 E/(V
			n or city street add	ress of well if ic	cated within city	•			
	roe, Ellis, I	•	Dalf Caanas						
			Belt Cooper	ative					
RR#, St. Add	dress, Box#	; P.O. B	ox 138				Board of Agrice	ulture, Divis	sion of Water Resources
			ansas 67637				Application Nu	mber:	
3 LOCATE	WELL'S LOC	CATON WITH	4 555511 05 00	MADI ETED ME		50 4 5	EVATION:		
AN "X" IN	N SECTION B	OX:							
	N N								ft.
1		i	WELL'S STATIC V	WATER LEVEL	23.98	ft. below land	d surface measured of	on mo/day/y	r U4/U 7/U7
	Nw -	- NE	Pump t	est data: Wel	l water was		ft. after	ຼ hours pເ	ımpinggpm
	!	!	Est. Yield NA	gpm: Wel	l water was		ft. after	_ hours pu	ımpinggpm
<u>≅</u> W	╼╵╮╼┺╾	E	Bore Hole Diamete	er 8.5 i	n. to	5.0	ft. and	in.	to ft. Injection well Other (Specify below)
7	_x	i	WELL WATER TO	BE USED AS:	5 Public wate	supply	8 Air condition	ning 11	Injection well
	sw	- SE			6 Oil field wat	er supply	9 Dewatering	12	Other (Specify below)
1 1	!	. I	2 Irrigation						
▼ ∟	L		Was a chemical/ba	acteriological sa	imple submitted	o Departmen	nt? Yes No _ 3	If yes,	mo/day/yr sample was
	S		submitted			W	Vater Well Disinfected	d? Yes	No X
5 TYPE OF	F BLANK CAS	SING USED:		5 Wrought Iro	on 8 Cor	crete tile	CASING JOIN	TS: Glued	Clamped
1 Ste					ement 9 Oth				ed
2)PV		4 ABS	,	7 Fiberglass			,		ded X
_				•	:		ff Dia	illea	in to
							ft., Dia		
Type of or	nt above land	SURTACEFI	USII WIOUIIL IN	., weight		DS./1	π. Wall thickness or	gauge No.	Schedule 40
TYPE OF SO		CKFUKATIOI	N MATERIAL: ss steel	5 Eiborolog-		7) PVC	10 Asbe:	sios-cemer : (enacify)	nt
2 Bra						D KIMIP (OK)	12 None	(specify)	n hola)
		TION OPENIN							11 None (open hole)
	ntinuous slot	_	Mill slot	6	Gauzed wrappe Wire wrapped	u	9 Drilled holes	'	i i stolie (open noie)
			Key punched		Torch cut			fv)	
		INTERVALS:				f f	From	ft to	ft.
OOKLENT	LIN OIGHED	MATERIALES.							ft.
CD/	AVEL BACK II	NITEONAL C.	F 2	50 # 45	8.0	۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰۰	. F10111		·''.
GRA	AVEL PACK II	NTERVALS:							ft.
			From	ft. to		π.	. From	ft. to	π.
GROUT	MATERIAL:	1 Neat o	ement 20	Cement grout	32	entonite	4 Other		
Grout Interv	als From	0.0	ft. to 0.5	ft. From	0.5 f	. to8	ft. From		ft. toft.
What is the	nearest source	e of possible	contamination:				estock pens		ndoned water well
1 Sep	otic tank		4 Lateral lines	7 Pi	t privy		el storage (former)		
	wer lines		5 Cess pool		ewage lagoon		rtilizer storage	16 Othe	er (specify below)
3 Wa	tertight sewer	lines			eedyard	13 Ins	ecticide storage		
Direction from well? Northwest How many feet? 740									
FROM	то	CODE			Lľ	THOLOGIC L	_OG		
0.0	18.0		wn silty clay, r						
18.0	25.0	Bro	wn clayey silt,	some round	led-subround	led gravel,	, wet @20'		
			_						
			Exception	on to K.A.R.	28-30-6(b) (1	and (e) a	pproved by D. Ta	ylor, KDI	HE-BOW.
									\sim
7 CONTRA	ACTOR'S OR	LANDOWNER							my furisdiction and was
	n (mo/day/yr)		04/02						de and belief. Kansas
Water Well	Contractor's L	icense No.		692	This	Water Well	Record was complete	ed gry/m/o/o	day/yr /05/25/07
	usiness name		Quad 9	State Service			by (signature)	'/' M	NC NI
						sas Departme	nt of Health and Environ	ment, Burea	u of Water, 1000 S W
							OWNER and retain one		