

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Ellis</u>		<u>SW</u> 1/4 <u>SW</u> 1/4 <u>NW</u> 1/4	<u>9</u>	T <u>13</u> S	R <u>20</u> E <u>(W)</u>
Distance and direction from nearest town or city street address of well if located within city? <u>10th & Monroe, Ellis, Ks.</u>					
2 WATER WELL OWNER:		Golden Belt Coop			
RR#, St. Address, Box # :		<u>10th & Monroe</u>			
City, State, ZIP Code :		<u>Ellis, Ks. 67637</u>			
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>30'</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>14'</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>12.64'</u> ft. below land surface measured on mo/day/yr <u>6-4-98</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm; Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8 1/2"</u> in. to <u>30'</u> ft., and in. to ft.			
TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded <u>2 PVC</u> 4 ABS 7 Fiberglass Threaded <u>X</u> Blank casing diameter <u>2.375</u> in. to <u>27 1/2'</u> ft. Dia. in. to ft. Dia. in. to SDR <u>13</u> ft. Casing height above land surface <u>Flush Mt.</u> in. weight lbs./ft. Wall thickness or gauge No. <u>SCH 40</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From <u>27 1/2'</u> ft. to <u>27 1/2'</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From <u>29 1/2'</u> ft. to <u>21'</u> ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From <u>21'</u> ft. to <u>3'</u> ft. From <u>3'</u> ft. to <u>0'</u> ft. From ft. to ft.			
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage <u>Fueler</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			
Direction from well? <u>In Old AST Area</u>		How many feet? <u>0'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Blk-dk brn clay fill, dry, no odor, few ls.rx. frag.			
4	8	Lt-med brn clay to silty clay, moist, no odor, firm.			
8	14	Green gray mottled silty clay to clayey silt, moist, firm to soft, slight odor.			
14	26	Gray fine-med grained sand, w/ some silt, wet at 14', mod odor.			
26	30	Tan fine-coarse sand w/ qtz/ls.rx. gravel, wet, slight odor, well graded.			
<u>F.H. OK'd by Don Taylor</u>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-27-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>6-4-98</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Becker</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4