WATER WELL RECORD	Form W	WC-5	Division of Water Resources App. No.	de a constantina de la constantina della constan	
1 LOCATION OF WATER WELL: County: Ellis	Fraction SE 1/4 SE 1/4 SE	1/4 1/4	Section Number Township No. Range Nu	umber _E VW	
Street/Rural Address of Well Location; if unknown, distance & direction			Global Positioning System (GPS) information:		
from nearest town or intersection: If at owner's address, check here			Latitude: (in decimal degrees)		
583 Vineyard Rd, Ellis, Ks		Longitude: (in decimal degrees)			
ooo viitoyata rai, miio, ra		Elevation:			
2 WATER WELL OWNER: Maria H			<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27		
Maria Horriburg		Collection Method:			
City Charles (ZID) Co. 1-			GPS unit (Make/Model:) Digital Map/Photo, Topographic Map, Land Survey		
Havs. K	(S 67601		Est. Accuracy: $\square < 3 \text{ m}$, $\square 3-5 \text{ m}$, $\square 5-15 \text{ m}$, \square		
3 LOCATE WELL					
WITH AN "X" IN 4 DEPTH OF	COMPLETED WEL	լ .60	ft.		
SECTION BOX: Depth(s) Ground	Depth(s) Groundwater Encountered (1).34				
N WELL'S STAT	WELL'S STATIC WATER LEVEL34				
Pump test data: Well water was 35					
EST. YIELD. 15gpm. Well water wasft. after					
W Bore Hole Diameter					
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)					
Irrigation I Industrial I Domestic-lawn & garden I Manitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No					
S If yes, mo/day/vr sample was submitted					
Water well disinfected? ✓ Yes ☐ No					
5 TYPE OF CASING USED: Steel V PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter 5 in to 60 ft Diameter in to ft Diameter in to ft					
Casing height above land surface. 24 in., Weight 2.91 lbs./ft., Wall thickness or gauge No21					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From 60 ft. to 30 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 60 ft. to 20 ft., From ft. to ft.					
From					
6 GROUT MATERIAL: Neat cement Cement grout Definite Other					
Grout Intervals: From .20 ft. to .0 ft., From ft. to ft., From ft. to ft., From ft. to ft.					
Septic tank					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well					
Direction from well			rom well		
FROM TO LITHOLOG	FIC LOG	FROM	TO LITHO. LOG (cont.) or PLUGGING IN	ITERVALS	
0 3 Top soil					
3 15 Gumbo clay 15 20 sand					
	**************************************			····	

25 40 Sand, gumbo mix 40 45 Rock		-			
45 60 Shale					
45 00 Shale		<u> </u>		*****	
		 			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) 1.1/4/11 and this record is true to the best of my knowledge and belief					
Kansas Water Well Contractor's License No. 0199 This Water Well Record was completed on the Incord to the Incord was completed on the Incord was completed w					
under the business name of Karsi Water Well Drilling and Service					
INSTRUCTIONS: Use typewriter or ball point nen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct professor and check the correct professor.					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					