

1 LOCATION OF WATER WELL: County: Ellis Fraction SW 1/4 SE 1/4 NE 1/4 Section Number 8 Township Number T 13 S Range Number R 20 EW

Distance and direction from nearest town or city street address of well if located within city? 1000 Washington, Ellis

2 WATER WELL OWNER: Ellis Stop 2 Shop RR#, St. Address, Box # : 1000 Washington City, State, ZIP Code : Ellis, Kansas 67637 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram showing a 2-mile square divided into four quadrants with an 'X' in the NE quadrant.] 4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 2120.03. Depth(s) Groundwater Encountered... WELL'S STATIC WATER LEVEL... Pump test data: Well water was NA ft. after... hours pumping... Est. Yield NA gpm... Bore Hole Diameter 8 in. to 25 ft., and... in. to... ft. WELL WATER TO BE USED AS: 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes... No [checked]; If yes, mo/day/yr sample was submitted... Water Well Disinfected? Yes No [checked]

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). CASING JOINTS: Glued, Clamped, Welded, Threaded [checked]. Blank casing diameter 2 in. to 15 ft., Dia. in. to... ft., Dia. in. to... ft. Casing height above land surface -4.32 in., weight... lbs./ft. Wall thickness or gauge No. Sch. 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft., From... ft. to... ft., From... ft. to... ft. GRAVEL PACK INTERVALS: From 13 ft. to 25 ft., From... ft. to... ft., From... ft. to... ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other Concrete. Grout Intervals: From 0 ft. to 1 ft., From 1 ft. to 13 ft., From... ft. to... ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? How many feet?

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-0.5 Concrete, 0.5-6 Clay, Silt, Sand, 6-11 Clay, silty, Brown, 11-17 Clay, v. silty, Brown, 17-20 Clay, v. silty, Lt. Brown mottled Lt. Gray, 20-25 Clay, v. silty, Gray. MW10R, Flushmount.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/5/2013 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527. This Water Well Record was completed on (mo/day/yr) 8/15/13 under the business name of GeoCore, Inc. by (signature) Dale Holt.