WATER WELL RECORD		Form W	WC-5		Division of Water Resources App. No.		
1 LOCATION OF WATER WELL:		Fraction				Range Number	
County: Norton (DRI)		MAIE MAN				R23 DE W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					ng System (GPS) is		
from nearest town or it	UWIICI S AUGUCOS, CIICCA	Latitude: (in decimal degrees) Longitude: (in decimal degrees)					
		Elevation:					
4 moles south, 1/4 moles west at Norton				<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: パート Schultz RR#, Street Address, Box #: 110 S Kansus RVと				Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code : Norton, K5 67654			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
City, State, 211 Code	.,			Est. Accuracy:	<3 m, 3-5 m,] 5-15 m, □>15 m	
3 LOCATE WELL							
WITH AN "X" IN	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 2.00					(2) A	
SECTION BOX:							
	Pump test data: Well water was						
NW NE	EST VIELD	ウナ onm Well water	r was	ft. after	hours pun	ming gpm	
W E	Bore Hole Dian	neter		ft., and i	n. to	.ft.	
	WELL WATER	TO BE USED AS:	Public wa	er supply 🔲 🤇	Geothermal []	Injection well	
SW SE		☐ Feedlot ☐	Oil field wat	er supply []	Dewatering []	Other (Specify below)	
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
S If yes, mo/day/yr sample was submitted							
1 mile Water well disinfected? \(\subseteq \) Yes \(\subseteq \) No							
5 TYPE OF CASING USED: Steel NOVC Other							
CASING JOINTS: Gleed Clamped Welded Threaded							
Casing diameter							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)							
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)							
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)							
SCREEN-PERFORATED INTERVALS: From 160 ft. to 200 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 2.5 ft. to 200 ft., From ft. to ft.							
From ft to ft From ft to ft							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From							
What is the nearest source							
Septic tank Sewer lines	Lateral lii Cesspool		Livestock			her (specify below)	
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well							
Direction from well				from well		•••••••	
FROM TO	LITHOLOG	GIC LOG	FROM	TO LITHO.	LOG (cont.) or PLU	JGGING INTERVALS	
0 8 Tag	Sall						
8 45 brow	en cley						
45 80 gree	~ cje) ; v	ditectory					
80 130 115	reley's	The sand					
130 160 Fony	sand; 5	0+7 50 70 Stin	 				
160 200 Sand	13 clas	1 201 1 4 1 5 9 1 0 1	 				
	47 610	07.18					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .89 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No7.5.4 This Water Well Record was completed on (mo/day/year) .8.7.5.4 under the business name of Galler Inc							
INSTRUCTIONS: Use typew	riter or hall noint ner	PLEASE PRESS FIRM	and PRINT AL	Dy (Signature)	nks and children the co-	of anguage Cand these course	
(white, blue, pink) to Kansas I	Department of Health	and Environment, Bureau	of Water, Geol	ogy Section, 1000 SW	Jackson St., Suite 420,	Topcka, Kansas 66612-1367.	
Telephone 785-296-5522. Sen http://www.kdheks.gov/waterwe	nd one copy to WA?	TER WELL OWNER and	retain one for	rour records. Include	fee of \$5.00 for each	constructed well. Visit us at	
I THE THE PARTY OF	VIS LINEALINGIS.					1) hite	
						V	