			ER WELL RECO	ORD Form WWC-5		a-1212 ID N				
1 LOCATIO	ON OF WA	TER WELL:	Fraction		Sect	ion Number	Township Numb	_	Number	
	SALINE		NE 1/4		1/4	12	т 13	s R 3	√ E/W	
		from nearest tov	vn or city street	address of well if locat	ed within city	/?				
	5500 N	8 YWH GLO.	1							
2 WATER	WELL OW		ARK HIKINS							
RR#, St. Ac	ddress. Box		EDGIHILL R				Board of Agricult	ture, Division of W	ater Resource	
City, State,		: SALI	(A,KS. 6740)1			Application Num			
3 LOCATE	WELL'S LC	CATION WITH 4	DEPTH OF C	OMPLETED WELL	90.'6"	ft. ELEVAT	ION:			
_	N SECTION	N BOX:	Depth(s) Ground	water Encountered 1	48.	ft. 2		.ft. 3	ft.	
	Ņ	\								
, ♦	! !		Pump	test data: Well water	was5	3 ft. aft	ter 3 h	ours pumping	apm	
	NW -	NE I	Est Yield 754	gpm: Well water	was	ft aft	ter h	ours numping	gp	
	X		Bore Hole Diame	terin. to	91	ft ar	nd	in to		
₩		1 1 1		O BE USED AS: 5 P				11 Injection well		
- "	!	! []					Dewatering	12 Other (Specif	v helow)	
	sw	- SF	2 Irrigation	4 Industrial 7 De	mestic (lawn	& garden) 10	Monitoring well			
	1		-				- ~~			
<u> </u>	1			acteriological sample sub	mitted to Dep			yes, mo/day/yrs sa	ample was sub	
E T/DE 0	S		mitted	* Minnesoth topo	0.0		Well Disinfected? Ye			
		CASING USED:		Wrought iron				S: Glued. 🖟 Cla	•	
1 Steel		3 RMP (SR)	_	Asbestos-Cement		specify below)		Welded		
_2 PVC	-	4 ABS 5	70	Fiberglass				Threaded	• • • • • • • • • • •	
Blank casii	ng diamete	r	in. to	Dia	in.	to	ft., Dia	in. to ವಿಗಾ	۰f	
Casing hei	ight above	land surface	Ļ [.] O in.	, weight 160			t. Wall thickness or ga	uge No	~9	
TYPE OF	SCREEN	OR PERFORATION			7 PVC		10 Asbesto			
1 Steel		3 Stainless		Fiberglass		P (SR)		pecify)		
2 Brass 4 Galvanized steel 6 Concrete ti					9 ABS		12 None us	12 None used (open hole)		
		DRATION OPEN	NGS ARE:		• •		3 Saw cut 11 None (open hole)			
	inuous slot		slot •025		rapped		9 Drilled holes			
2 Louv	ered shutte	er 4 Key	/ punched	7 Torch			10 Other (specify)		π.	
SCREEN-I	PERFORA	TED INTERVALS	S: From. 7.9. 9.	tt. to	7.9 . 9	ft., From .	• • • • • • • • • • • • • • • • • • • •	ft. to	ft.	
(SBAVEL P	ACK INTERVALS	From 22	ft. to ft. to		ft From	62		r 6''' · · · · · · π.	
`	UNIAVELI	AON INTERVAL		ft. to						
6 GROUT	MATERIA	l: 1 Noat oor	mont	Coment grout	2 Pontoni	to 4.0	thor			
Grout Into	rvale: Ero	m 0	"ft to 22 '	Cement grout	59 5 benten	$\frac{10}{10}$ 62	ft From	ft to	4	
		source of possible								
		•				10 Livestock pens		14 Abandoned water well 15 Oil well/Gas well		
1 Septic tank 4 Lateral				11 Fuel stora		•	• • • • • • • • • • • • • • • • • • • •			
2 Sewer lines 5 Cess po 3 Watertight sewer lines 6 Seepage				8 Sewage lag		goon 12 Fertilizer sto		storage 16 Other (specify below) storage OPEN PASTURE NONE APPARENT		
		er lines 6 Seepa	ge pit	9 Feedyard				rith Totha Tions	- '** '**********	
Direction for						How many				
FROM	то		THOLOGIC LOC		FROM	ТО	PLUGGI	NG INTERVALS		
0	12		CLAY LAYS	RS MIXED						
12	16	CLAY GRA								
16	17	SANDSTON								
17	19	CLAY GRA								
19	31		WITH CLAY							
31	62	SANDSTON	E REDISH BE	ROWN SOFT						
62	91	SANDSTON	E LIGHT TAI							
91		SHALE GRA	AY HARD							
										
7 CONTRA	CTOR'S O	R I ANDOWNED	S CERTIFICATIO	ON: This water well wa	s (1) constru	cted (2) recor	estructed or (3) plugg	ed under my juried	iction and was	
completed a	on (ma/da	(voer) 7-5-0	02	ON: This water well wa	עוופוושייי <i>ר</i> -	nd this record	is true to the best of	ou unuer my junsu my knowladaa asd	holiof Verrer	
				This Water Well				7-5-04 and	Deliel, Nansas	
water well	Contractor	s Licence No me of PUSTIM		mis water wei BRVTAS	necora was		1 1 10 11		• • • • • • • • • • • • • • • • • • • •	
unaer the bi	usiness nai	LIG OL TOTAL	ل ا غاتي ا عاتي			by (sigr	nature) Deef	testen	1/15	
				LYand <u>PRINT</u> clearly. Please fil			7	· ·	ent of Health and	
Environment	t, Bureau of Wa	ter, Topeka, Kansas 666	320-0001. Telephone 78	5-296-5524. Send one to WATE	R WELL OWNER	and retain one for	your records. Fee of \$6.00 for a	each constructed well.		