


WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL: County: Saline Fraction: NE 1/4 SE 1/4 NW 1/4 Section Number: 17 Township Number: T 13 S Range Number: 3W E/W

Distance and direction from nearest town or city street address of well if located within city? 3 1/2 Mi. N + (3 1/2 Mi. W.) of Salina

WATER WELL OWNER: Steve Coffman
 RR#, St. Address, Box #: Rt 2
 City, State, ZIP Code: Salina Kansas 67401
 Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: DEPTH OF COMPLETED WELL: 71 ft. ELEVATION: 1235



Depth(s) Groundwater Encountered 1. 63 ft. 2. . ft. 3. . ft.
 WELL'S STATIC WATER LEVEL 215 ft. below land surface measured on mo/day/yr 8/24/81
 Pump test data: Well water was ND ft. after 1/2 hours pumping 50 gpm
 Est. Yield 70 gpm; Well water was . ft. after . hours pumping . gpm
 Bore Hole Diameter 6 in. to 71 ft., and . in. to . ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped .
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded .
 7 Fiberglass Threaded .
 Blank casing diameter 4 in. to 68 ft., Dia . in. to . ft., Dia . in. to . ft.
 Casing height above land surface 12 in., weight . lbs./ft. Wall thickness or gauge No. SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) .
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) .

SCREEN-PERFORATED INTERVALS: From 68 ft. to 71 ft., From . ft. to . ft.
 From 3 ft. to . ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 5-0 ft. to 71 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .
 Grout Intervals: From 3 ft. to 13 ft., From . ft. to . ft., From . ft. to . ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? southeast How many feet? 120

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	52	Clay, gray & green			
52	63	Silt, sandy, gray			
63	71	Gravel + sand, fine to coarse			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/24/81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 126. This Water Well Record was completed on (mo/day/yr) 8/26/81 under the business name of Hydraulic Drilling Co by (signature) [Signature]
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.