

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: SALINE Fraction SE 1/4 SW 1/4 SW 1/4 Section Number 14 Township Number T 13 S Range Number R 4 W E/W Distance and direction from nearest town or city street address of well if located within city? 6330 W. SHIPTON RD. Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: PAUL BURGER RR#, St. Address, Box #: 1845 ROBERTS City, State, ZIP Code: SALINA, KS 67401

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S 4 DEPTH OF COMPLETED WELL: 45 ft. Depth(s) Groundwater Encountered (1) 12 ft. (2) (3) WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr 08-21-07 Pump test data: Well water was ... ft. after ... hours pumping ... gpm Est. Yield: 12 gpm: Well water was ... ft. after ... hours pumping ... gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well LIVESTOCK Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr Sample was submitted. Water well disinfected? Yes X No

5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 5 in. to 25 ft., Diameter 160 lbs./ft. Wall thickness or guage No. 30226 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 1025 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 25 ft. to 45 ft. GRAVEL PACK INTERVALS: From NO ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 5 ft. to 25 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 16 Other (specify) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well below 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/gas well Direction from well? NORTH WEST How many feet? 25

Table with 2 main columns: LITHOLOGIC LOG and PLUGGING INTERVALS. Rows include depth intervals (0-2, 2-12, 12-22, 22-40, 40-45) and lithology descriptions (TOP SOIL, CLAY TAN, CLAY GRAY, SANDSTONE TAN HARD, SHALE GRAY). Plugging interval note: SHALE BOOT SET AT 25'

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-21-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 387 This Water Well Record was completed on (mo/day/year) 08-21-07 under the business name of PASTORAL PUMP SERVICE by (signature) Paul Burger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.