WATE	R WE	LL RECORD	Form W	WC-5	Division of Water	r Resources App. No	o. L	
Cou	nty: Wa		Fraction SE ¼ NW ¼ SV		Section Number 25	Township No. T 13 S	Range Number R \$40 □E V W	
		Address of Well Location;	f unknown, distance	Global Positioning	System (GPS) in	formation:		
1		town or intersection: If at o		Latitude: .38,89016. (in decimal degrees)				
From Sharon Springs, 1/2 mi S and 1.7 mi E					Longitude: -101.72057 (in decimal degrees) Elevation: 3411			
2 WATER WELL OWNER: Jimmy Baehler					Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27 Collection Method:			
RR#, Street Address, Box #: PO Box 564					☐ GPS unit (Make/Model: Garmin GPS 5			
City, State, ZIP Code : Sharon Springs, KS 67758					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☑ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 50 ft.								
	Depth(s) Groundwater Encountered (1).31 ft (2) ft (3)							
520	SECTION BOX: Depth(s) Groundwater Encountered (1).31							
	Pump test data: Well water was 36							
NI	NW NE EST. YIELD. 40gpm. Well water was							
w	T							
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SN	SW SE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
1		☐ Irrigation	☐ Industrial ☐	Domestic-lav	n & garden 🔲 Mo	nitoring well		
	Was a chemical/bacteriological sample submitted to Department? Yes V No							
	S If yes, mo/day/yr sample was submitted							
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5 in. to .50 ft., Diameter ft., Diameter ft., Diameter ft.								
Casing height above land surface. 24 in., Weight 2.64 lbs./ft., Wall thickness or gauge No. 0.281								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From30								
Fromft. to								
GRAVEL PACK INTERVALS: From								
From ft. to ft., From ft. to ft.								
From								
Grout Intervals: From								
What is the nearest source of possible contamination:								
✓ Septic tank								
✓ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ✓ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
Direc	tion from	n well West		. Distance f	rom well7.0.0	• • • • • • • • • • • • • • • • • • • •		
FROM	ТО	LITHOLOG	IC LOG	FROM	TO LìTHO. LO	G (cont.) or PLUC	GGING INTERVALS	
0	28	_clay						
28	30	sandy clay						
30	39	sand		-				
39	50	shale						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .04/05/2014 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No213 This Water Well Record was completed on (mo/day/year) .04/28/2014								
under the business name of Kemp's Well Service by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one conv to								
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								

http://www.kdheks.gov/waterwell/index.html