WATER WELL RECORD			Form WV	VC-5	Div	vision of Wate	r Resources App. N	o	
1 LOCATION OF WATER WELL: County: Wallace		Fraction NW 1/4 SE 1/4 SE	1/4 SW 1/4	Section	on Number 22	Township No. T 13 S	Range Number R 40 □E ☑W		
	Street/Rural Address of Well Location; if unknown, distance & direction						System (GPS) in		
		own or intersection: If at o		Latitu	Latitude: .38,90250(in decimal degrees)				
102 E Highway 40					Longitude: 101.75207 (in decimal degrees)				
Sharon Springs, KS					Eleva	Elevation: 3474.27			
2 WATER WELL OWNER: Erik Howell						Datum: ☑ WGS 84, ☐ NAD 83, ☐ NAD 27 Collection Method:			
RR#, Street Address, Box #: PO Box 264					GPS unit (Make/Model:)				
City, State, ZIP Code : Sharon :			Springs, KS 67748	Drings, KS 67748 Digital Map/Photo, Topographic Map, Lar Est. Accuracy: Est. Accuracy: 3 -5 m, 5 -15 m, 5 -15					
3 LOCATE WELL						ccuracy: 🔽 <	3 m, <u></u> 3-5 m, <u></u>] 5-15 m, ∐>15 m	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 38									
SECT	SECTION BOX: Depth(s) Groundwater Encountered (1).28							(3) ft.	
WELL'S STATIC WATER LEVEL. 28.54ft. below land surface measured on mo/day/yr. 1.1/12/14							lay/yr 1.1/12/14		
Pump test data: Well water wasft. after							ping gpm		
-NW - -NE - EST. YIELDgpm. Well water wasft. after								iping gpm	
$ $ w $ $ $ $	W								
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well									
Was a chemical/bacteriological sample submitted to Department? ✓ Yes ☐ No									
S If yes, mo/day/yr sample was submitted.11/12/14									
water will distinct the rest of the									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter .2 in. to .38 ft., Diameter in. to									
Casing neight above land surface									
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)									
☐ Continuous slot ☐ Galize wrapped ☐ Torch cut ☐ Drifted holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
GRAVEL PACK INTERVALS: From									
From									
Grout Intervals: From .1									
What is the nearest source of possible contamination:									
				Livestock Fuel storage					
Sewer lines Cesspool									
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ LUS I Site ☐ Direction from well ☐ Distance from well Distance from well ☐ Distance from well Distance f									
FROM	ТО	LITHOLOG		FROM	TO			UGGING INTERVALS	
0	1	Concrete							
1	22	Clay, silty, brown					*****		
22	27	Shale, brown						www.	
27	38	Shale, grey				BANA/4 A			
	-					MW14	g ID: 0050158		
-				 		TOTIL TO	4 ID. 0000 100		
		1							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .1.1/1.1/1.4 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 594 This Water Well Record was completed on mo/day lear) 1/15/14									
INSTRUC	CTIONS:	Use typewriter or ball point pe	n. PLEASE PRESS FIRMLY	and PRINT c	early. Ple	ease fill in blank	s and check the correc	t answers. Send one copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.									
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									