LOCATION OF W			Form WWC-5			lila a u	Range Nu		
LOCATION OF WA	1 4	on 1 14 SW 14 NW		tion Number	Township N	Number S	R 5	ımoer E∕W	
stance and direction	n from nearest town or city s	treet address of well if located	within city?		- 75				
600' N a	nd 400' E of 1	intersection of	[I-70	and	Me Gaver	n			
WATER WELL O	WNER: Don Donova	7	-	-	-				
	0x # : 120 W Elm S				Board of	Agriculture, D	Division of Wate	r Resourc	
ity, State, ZIP Code Junction City, KS 66441-3709					Application Number:				
LOCATE WELL'S	LOCATION WITH 4 DEPTH	OF COMPLETED WELL	4.5	ft. ELEVA	TION: 1.3.9	٥			
AN "X" IN SECTION	N Depth(s) C	Groundwater Encountered 1							
	WELL'S S	STATIC WATER LEVEL / 2	ل ft. b	elow land sur	face measured o	n mo/day/yr			
NW	NF	Pump test data: Well wate						-	
X	1 1 1	gpm: Well wate				•	. •	•	
w - !		Diameter . 8. 2/8 in. to					to	· • · · · · ·	
"	I : I :		5 Public water	.,,,	8 Air conditioning	•	Injection well		
SW	SE (2)Dor		6 Oil field wa		9 Dewatering		Other (Specify t	•	
1 !	2 Irrig	gation 4 Industrial emical/bacteriological sample s	_	-	10 Monitoring we	7			
<u> </u>	s was a crie	emica/bacteriological sample s	Submitted to Di		ter Well Disinfect		No No	Die was si	
TYPE OF BLANK		5 Wrought iron	8 Concre				I Clamp	ed .	
1 Steel	3 RMP (SR)	6 Asbestos-Cement		(specify below			ed		
2 PVC	4 ABS	7 Fiberglass		` ' '	•,		ded		
ank casing diamete	er 5 in. to	25 ft., Dia	in. to		ft., Dia	i	in. to	1	
_	4 4 4	in., weight							
YPE OF SCREEN	OR PERFORATION MATERIA	AL:	∂ PV	С	10 A s	bestos-ceme	nt		
1 Steel	3 Stainless steel	5 Fiberglass	8 RM	IP (SR)	11 Ot	her (specify)			
2 Brass	4 Galvanized steel	6 Concrete tile	9 AB	S	12 No	ne used (op	en hole)		
REEN OR PERFO	PRATION OPENINGS ARE:	5 Gauze	ed wrapped		8 Saw cut		11 None (ope	n hole)	
1 Continuous s			wrapped		9 Drilled holes				
2 Louvered shu		7 Torch			10 Other (speci	fy)			
CREEN-PERFORA	TED INTERVALS: From.		73	ft., Froi	m	ft. to)		
	From.	ft. to	116	ft., Froi	m	ft. to)		
GRAVEL P	ACK INTERVALS: From.	· -	G		m				
ODOUT MATERIA	From	ft. to	3 Bento	ft., Fro	m Other . Com. j	ft. to			
GROUT MATERIA rout Intervals: Fr		2 Cement grout 2.3 ft., From C) spento	to 2	Other . Corn.p.	MCT E.C.	·Cucy		
	source of possible contaminat	-	K		tock pens		candoned water		
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuel	•		il well/Gas well	WCII	
2 Sewer lines 5 Cess pool		• •	8 Sewage lagoon		12 Fertilizer storage		Other (specify below)		
	wer lines 6 Seepage pit	9 Feedyard			ticide storage		nknown		
irection from well?				How mai	J				
ROM TO	LITHOL	OGIC LOG	FROM	TO		LUGGING IN	NTERVALS		
0 2	Brown clay								
2 13 13 13.5	Red Brown cli								
	Brown Sandsto								
3.5 27	Bed Brown San	· -							
27 44	Brown Sandsto	<u>-</u>							
44 45	Gray to Light (Gray clay							
				<u> </u>			STREET, STREET		
			 						
	AND						THE PERSON NAMED IN SECURIOR STREET		
									
									
CONTRACTORS	OR LANDOWNER'S SECTION	FICATION: This water well wa	200	otad (0)	unatruoted (C)	nlugged ·	or my hudadiat		
	y/year) 9/26/9.7	FIGATION: This water well wa							
empieted on (mo/da ater Well Contracto		7 This Water W			rd is true to the b) 7	ner. Kans	
ater well Contractor der the business n		Services Inc.	en necord wa	s completed of by (signat			Z		
		•	60 in 1-11			~ / / (%	50014		
	typewriter or ball point pen. <u>PLEASE i</u> ment, Bureau of Water, Topeka, Kans	PRESS FIRMLY and PRINT clearly. Ple sas 66620-0001. Telephone: 913-296-5						paπment	