


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Lincoln		SW 1/4 SW 1/4 SE 1/4	4	T 13 S	R 8 E/W
Distance and direction from nearest town or city street address of well if located within city? 1 South, 3 West, 5 South, 1/2 West of Lincoln					
2 WATER WELL OWNER: Paul Mannel RR#, St. Address, Box #: Ellsworth, Kansas 67439 City, State, ZIP Code: Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 80 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr 2/6/1984 Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield 30 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 110 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No XXXX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XXXX No			
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X2 PVC 4 ABS 7 Fiberglass Threaded XXX Blank casing diameter 5 in. to 90 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 12 in. weight 3 lbs./ft. Wall thickness or gauge No. 258 TYPE OF SCREEN OR PERFORATION MATERIAL: XXXX7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped XXXX8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 90 ft. to 110 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 14 ft. to 110 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: XXXX Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 14 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? West Creek How many feet? 400					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (XX) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/6/1984 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 359 This Water Well Record was completed on (mo/day/yr) 2/17/1984 under the business name of Daryl Cox & Sons Inc. by (signature) Daryl Cox INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					