

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <b>SALINE</b>	<b>SE 1/4 NW 1/4 NW 1/4</b>	<b>24</b>	<b>T 140S</b>	<b>R 3E</b>


Distance and direction from nearest town or city street address of well if located within city?

**826 S. Sante Fe****3**

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Application Number:
City, State, ZIP Code :	

**Dorothy Smith**  
**826 S. Sante Fe**  
**Salina, KS 67401****1230**

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <b>56</b> ft. ELEVATION: <b>1230</b>
------------------------------------------------------	-----------------------------------------------------------------

Depth(s) Groundwater Encountered 1. **33** ft. 2. **33** ft. 3. **33** ft.WELL'S STATIC WATER LEVEL **33** ft. below land surface measured on mo/day/yr **10-18-98**Pump test data: Well water was **34** ft. after **1** hours pumping **15** gpmEst. Yield **30** gpm Well water was **34** ft. after **1** hours pumping **15** gpmBore Hole Diameter **8 1/2** in. to **35** ft., and **5 1/2** in. to **56** ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes **X** No **X**; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes **X** No **X**

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <b>X</b> Clamped
------------------------------	----------------	-----------------	---------------------------------------

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded

Blank casing diameter **5** in. to **46** ft., Dia **160LB** in. to **56** ft., Dia **50R26** in. to **56** ft.Casing height above land surface **15** in., weight **160LB** lbs./ft. Wall thickness or gauge No. **50R26**

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From **46** ft. to **56** ft., From **56** ft. to **56** ft.GRAVEL PACK INTERVALS: From **21** ft. to **35** ft., From **37** ft. to **56** ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From **0** ft. to **21** ft., From **35** ft. to **56** ft., From **37** ft. to **56** ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? **EAST**How many feet? **90**

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
------	----	----------------	------	----	--------------------

0'	2'	Fill Dirt			
----	----	-----------	--	--	--

2'	34'	Brown clay			
----	-----	------------	--	--	--

34'	36'	Grey clay			
-----	-----	-----------	--	--	--

36'	40'	Brown clay + SAND mixed			
-----	-----	-------------------------	--	--	--

40'	56'	Coarse SAND AND GRAVEL			
-----	-----	------------------------	--	--	--