

1 LOCATION OF WATER WELL: County: Ellsworth Fraction NE 1/4 SW 1/4 SW 1/4 Section Number 25 Township Number T 14 S Range Number R 10W E/W

Distance and direction from nearest town or city street address of well if located within city? 4 E, 1 N of Wilson, Kansas

2 WATER WELL OWNER: Betty Belton RR#, St. Address, Box #: 1007 N. Grand (P.O. 445) Board of Agriculture, Division of Water Resources City, State, ZIP Code: Ellsworth, Kansas 67439 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is in the SW quadrant.] 4 DEPTH OF COMPLETED WELL: 51 ft. ELEVATION: Unknown. WELL'S STATIC WATER LEVEL: 32 ft. below land surface measured on 10/21/94. Pump test data: Well water was ... ft. after ... hours pumping ... gpm. Est. Yield 12 gpm: Well water was ... ft. after ... hours pumping ... gpm. Bore Hole Diameter 7.7/8 in. to 51 ft. and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes No. If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. Blank casing diameter 5 in. to 21 in. Dia. in. to in. Dia. in. to in. Casing height above land surface 12 in., weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 21 ft. to 51 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 51 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Old Homestead Direction from well? North How many feet? 600

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Row 1: 0, 21, Top soil and clay, FROM, TO. Row 2: 21, 51, Sand and gravel, FROM, TO.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/21/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186. This Water Well Record was completed on (mo/day/yr) 10/24/94 under the business name of Kelly's Water Well Service, Inc. by (signature) [Signature]