WAT]	ER WEL	L RECORD	Form WWC-5	Division of Water Resources App. No.
1 LC	CATION	OF WATER WELL:	Fraction	Section Number Township No. Range Number
Co	unty: Russ	ell	NE 1/4 SW 1/4 NW 1/4 SW	
Str	eet/Rural A	ddress of Well Location;	if unknown, distance & direction	Global Positioning System (GPS) information: Latitude: .38,817,971 (in decimal degrees)
fro	m nearest to	own or intersection: If at	owner's address, check here 🗸	Longitude: 98.593082 (in decimal degrees)
				Elevation:
				Datum: WGS 84, NAD 83, NAD 27
		LL OWNER: Gary H		Collection Method:
		ddress, Box #: 3837 19		☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
Ci	ty, State, Z	P Code : Dorrand	ce, Ks. 67530	Est, Accuracy: $\square < 3 \text{ m}$ , $\square 3-5 \text{ m}$ , $\square 5-15 \text{ m}$ , $\square > 15 \text{ m}$
3 10	CATE WE			
	TH AN "X"	IN 4 DEPTH OF	COMPLETED WELL 148.	3 ft.
SE	CTION BO	X: Depth(s) Groun	dwater Encountered (1)	ft. (2) ft. (3) ft.
	N	WELL'S STAT	IC WATER LEVEL	ft. below land surface measured on mo/day/yr. 2/12/2015
		Pump	test data: Well water was	ft. after
	NW   NI	3 " "	ogpm. wen water was	ft., andin. toft.
W		E   Bore Hole Dian	TO BE USED AS: To Public	water supply Geothermal Injection well
x			Feedlot Oil field	water supply Dewatering Other (Specify below)
C.	SW   SI	Irrigation	☐ Industrial ☑ Domestic	c-lawn & garden  Monitoring well
L		Was a chemical	/bacteriological sample submitte	red to Department?  Yes  No
	S		/day/yr sample was submitted	
15.00 PM	1 mile	Water well disi	nfected? 🔽 Yes 🗌 No	
5 TYPE OF CASING USED: Steel PVC Other				
CASING JOINTS: Glued Clamped Welded Threaded				
Casing diameter 5 in. to ft., Diameter in. to ft., Diameter in. to ft.				
Casing height above land surface				
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Specify)				
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)				
SCREEN OR PERFORATION OPENINGS ARE:				
Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole) Louvered shutter  Key punched  Wire wrapped  Saw cut  Other (specify)				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)				
SCREEN-PERFORATED INTERVALS:         From				
GRAVEL PACK INTERVALS: From 20 ft. to 148 ft., From ft. to ft.				
From				
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other				
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other				
What is the nearest source of possible contamination:				
Septic tank				
	Watertig	ht sewer lines Seepage		izer storage Oil well/gas well
D	rection from	n well West	Dista	ance from well100.ft
FRO	M TO	LITHOLO	GIC LOG FROM	M TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0	1	Topsoil		
1	19	Clay, brown		
19	38	Gravel, coarse w/clay		
38	121	Shale, gray		
121	150	Sandstone		
-				
7 CC	NTRACT	OR'S OR LANDOWNE	R'S CERTIFICATION: This	s water well was 🗸 constructed, 🗌 reconstructed, or 🗌 plugged
under my jurisdiction and was completed on (mo/day/year) 2/12/2015 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 897. This Water Well Record was completed on (mo/day/year) 2/19/2015				
under the business name of Peterson McNett Drilling, Inc. by (signature)				
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.				
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, 1 opera, Ransas 60012-1307.  Telephone 785-296-5524 Send one conv. to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at				

http://www.kdheks.gov/waterwell/index.html