			WATE	ER WELL RI	ECORD	Form WWC-	·5 KSA 82	a-1212				
1 LOCATI		TER WELL:	Fraction			Se	ection Numbe	r Towns	hip Number		Range N	umber
County:		ssell	SE 1/2		1/4 ST	/4	7	J	Li S		R 11	<b>-</b> €/W
		from nearest towr	or city street a ( <b>No stree</b> t			ed within city?	)					
			Sprinkle									
	R WELL OW		• Oprimale	3				_				_
	Address, Bo		ance, Kans	ses 676	53),				d of Agricultu		on of Wate	r Resources
City, State	, ZIP Code	OCATION WITH				70		Appl	ication Number	er:		
AN "X"	IN SECTIO	OCATION WITH 4 N BOX:	DEPTH OF	COMPLETE	D WELL.		ft. ELEV	ATION:				
		<del>'</del>   [	Depth(s) Ground	dwater Enco	untered 1	).0	ft.	2	1	t. 3 	mil 8.	1985 <sup>ft.</sup>
1	i		WELL'S STATIC	WAIERL	EVEL	.4Y n.	below land su	urface measur	red on mo/day	//yr	20	
	NW	NE	Pum 20 20	ip test data:	Well wate	er was	<del>Ψπ.</del>	after	hours	pumpin	g <del></del>	gpm
1	!	! ! !!	Est. Yield 2.	9 gpm:	well wat	er was 70	π.	atter	hours	pumpin	g	gpm
Mile M	<u> </u>		Bore Hole Diam WELL WATER		-							π.
-	i		1 Domestic		edlot		ter supply		-	•	tion well	h a la\
	SW	SE	2 Irrigation		dustrial			9 Dewaterin				
	! *	!    ,	•					10 Observati				
į L			Vas a chemical	Dacteriologic	cai sample	Submitted to t	-					pie was sub
5 TYPE (	OF BLANK	CASING USED:	nitted 2	5 Wrough	nt iron	Q Cons	rete tile	ater Well Disi	ntected? Yes IG JOINTS: G		No	
1 St		3 RMP (SR	-		os-Cement		rete tile r (specify belo					
2 P\		4 ABS		7 Fibergla								
		<b>5</b> i	n. to . 50	, i ibeigia	Dia	in t	0	ft Dia		in to		
Casing he	ight above l	and surface	18	in weight	160		lhs	/ft. Wall thick	ness or daud	e No	.2	6
		R PERFORATION				7 P			0 Asbestos-c			
1 Ste		3 Stainless		5 Fibergla	ass	·	MP (SR)		1 Other (spec			
2 Br	ass	4 Galvanize		6 Concret		9 A			2 None used	-		
SCREEN	OR PERFO	RATION OPENING	S ARE: 8		5 Gauz	ed wrapped		8 Saw cut			None (ope	en hole)
1 Cc	ontinuous slo	t 3 Mill	slot			wrapped		9 Drilled h			(-	,
2 Lo	uvered shut	ter 4 Key	punched		7 Torch	n cut		10 Other (s	specify)		. <i></i>	
SCREEN-I	PERFORAT	ED INTERVALS:	From	50	ft. to .	70	ft., Fro	om		ft. to		
			From	<b></b> .	ft. to .	<b>.</b>	ft., Fro	om		ft. to		<i></i> ft.
(	GRAVEL PA	CK INTERVALS:	From	20	ft. to .	70	ft., Fro	om		ft. to		
<b>_</b>			From		ft. to		ft., Fro	om		ft. to		ft.
6 GROUT	r Material		ment	2 Cement				Other				
Grout Inter		m <b>0</b> f			rom	ft.	to	ft., Fro	om	ft	. to	
		ource of possible c						stock pens	-		oned wate	
1 Septic tank 4 Lateral lines 7 Pit privy							11 Fuel storage 15 Oil well/Gas well					
1								6 Other	(specify be	elow)		
l .	_	er lines 6 Seepa	ge pit	9 F	Feedyard			cticide storag	e			
Direction f	rom well?		LITHOLOGIC	100		FROM	How ma	any feet?	LITUOI	OGIC L	00	
O	3	Topsoil	LITHOLOGIC	LOG		FRON	1 10		LITHOL	OGIC L	OG	
3	35	Brown cla										
35	49	Sand	·									
49	56	Gray clay										
56	58	Rock										
58	61	Blue cla	<b>o</b> r									
61	68	White cla		-								
68	70	Shale										
	'											
								· · · · · · · · · · · · · · · · · · ·				
7 CONTE	RACTOR'S	OR LANDOWNER'	S CERTIFICAT	ION: This w	ater well w	as (1) constr	ucted. (2) red	onstructed. or	r (3) pluaaed	under m	v jurisdictio	on and was
completed	on (mo/day	year) . <b>April</b> .	8, 1985					ord is true to t				
		s License No						on (mo/day/)				
under the	business na	me of <b>Karst</b>	Water Well	l Servic	e		by (signa	ature)	1,0 \$	GI 1	1	)
INSTRUC	TIONS: Use	typewriter or ball pe	oint pen. PLEAS	SE PRESS	FIRMLY an	d <i>PRINT</i> clea	rly Please fill	in blanks upo	ettine or circle	the cor	rect answe	rs. Send top
three copie	es to Kansas	Department of Hea	Ith and Environ	ment, Divisio	n of Enviror	nment, Enviro	nmental Geold	ogy Section, To	opeka, KS 666	20. Sen	d one to WA	ATER WELL