

1 LOCATION OF WATER WELL: County: Russell Fraction SE 1/4 SE 1/4 NW Section Number 26 Township Number T 14 S Range Number R 12W E/W

Distance and direction from nearest town or city street address of well if located within city? 2 S, 2 W of Dorrance, Kansas

2 WATER WELL OWNER: Melvin Steinle RR#, St. Address, Box #: Route 1 City, State, ZIP Code: Dorrance, Kansas 67634 Board of Agriculture, Division of Water Resources Application Number: None

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants and an 'X' in the center. A vertical scale on the left indicates 1 Mile.

4 DEPTH OF COMPLETED WELL: 115 ft. ELEVATION: Unknown. Depth(s) Groundwater Encountered: 1. 51 ft. 2. 51 ft. 3. 10/21/83 ft. WELL'S STATIC WATER LEVEL: 51 ft. below land surface measured on mo/day/yr. Pump test data: Well water was 50 gpm after 8 hours pumping. Est. Yield: 8 gpm. Bore Hole Diameter: 8 in. to 115 ft. and 8 in. to 115 ft. WELL WATER TO BE USED AS: 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below). Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes XXX

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-cement, 11 Injection well, 12 Other (Specify below). CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 95 ft., Dia 12 in. to 2.8 in. Dia 2.8 in. to Sch. 40 ft. Casing height above land surface: 12 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 95 ft. to 115 ft., From 115 ft. to 115 ft., From 115 ft. to 115 ft. GRAVEL PACK INTERVALS: From 10 ft. to 115 ft., From 115 ft. to 115 ft., From 115 ft. to 115 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? South How many feet? 200

LITHOLOGIC LOG table with columns FROM, TO, and LITHOLOGIC LOG. Entries: 0 to 50 Clay, 50 to 115 Sand Rock.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/21/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 12/5/83 under the business name of Kellys Water Well Service by (signature) Kellys Water Well Service

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL