


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 11 Township Number T 14 S Range Number R 18 E
 County: Ellis

Distance and direction from nearest town or city street address of well if located within city?
3/4 mi. South on Cantaberry + old Hwy 40 Hays Ks. 67601

2 WATER WELL OWNER: KORRY BOOS
 RR#, St. Address, Box #: 212 Pershing Ct Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Hays KS. 67601 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 38 ft.
 Depth(s) Groundwater Encountered 1. 38 ft. 2. 42 ft. 3. 42 ft.
 WELL'S STATIC WATER LEVEL: 42 ft. below land surface measured on mo/day/yr 7/8/95
 Pump test data: Well water was 10 ft. after 1.5 hours pumping 20 gpm
 Est. Yield 20 gpm: Well water was 10 ft. after 1.5 hours pumping 20 gpm
 Bore Hole Diameter: 10 in. to 10 in. and 10 in. to 10 in.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 5 in. Dia. 5 in. to 5 in. Dia. 5 in. to 5 in. Dia. 5 in. to 5 in. Dia.
 Casing height above land surface 18 in. weight 18 lbs./ft. Wall thickness or gauge No. SPR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 6 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From 40 ft. to 60 ft., From 40 ft. to 60 ft., From 40 ft. to 60 ft.
 GRAVEL PACK INTERVALS: From 35 ft. to 60 ft., From 35 ft. to 60 ft., From 35 ft. to 60 ft., From 35 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 24 ft., From 4 ft. to 24 ft., From 4 ft. to 24 ft., From 4 ft. to 24 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? East How many feet? 75-100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Top soil			
5	38	brown clay			
38	42	fine grey sand w/ brown clay			
42	48	brown clay			
48	58	med to fine grey + red sand			
58	60	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/8/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 276 This Water Well Record was completed on (mo/day/yr) 7/8/95 under the business name of HUSA Water Well by (signature) John Doe