


1 LOCATION OF WATER WELL: County: Ellis Fraction: NW 1/4 SE 1/4 NE 1/4 Section Number: 15 Township Number: T 14 S Range Number: R 18 E 1

Distance and direction from nearest town or city street address of well if located within city? 1 1/2 miles North Munjor Ks.

2 WATER WELL OWNER: Alan Steerlien
 RR#, St. Address, Box #: Rt. #1 Box 881
 City, State, ZIP Code: Heyes Ks 67601
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 59 ft. ELEVATION: N/A

Depth(s) Groundwater Encountered 1. 23 ft. 2. 23 ft. 3. 23 ft.
 WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 7-22-94
 Pump test data: Well water was 32.60 ft. after 1/2 hours pumping 18 gpm
 Est. Yield 30 gpm Well water was 31.05 ft. after 1 hours pumping 18 gpm
 Bore Hole Diameter: 3 9/16 in. to 5 9/16 ft., and 5 9/16 in. to 5 9/16 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:
 1 Steel 2 Brass 3 RMP (SR) 4 Galvanized steel 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) 10 PVC 11 Other (specify below) 12 None used (open hole)
 Blank casing diameter 5 in. to 5 in. Dia. 39 in. to 39 in. Dia. 39 in. to 39 in. Dia. 39 in. to 39 in. Dia.
 Casing height above land surface 24 in., weight 24 lbs./ft. Wall thickness or gauge No. SDR 21

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Mill slot 3 Gauzed wrapped 4 Key punched 5 Wire wrapped 6 Torch cut 7 Saw cut 8 Drilled holes 9 Other (specify) 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 39 ft. to 39 ft. From 39 ft. to 39 ft. From 39 ft. to 39 ft. From 39 ft. to 39 ft.
 GRAVEL PACK INTERVALS: From 59 ft. to 20 ft. From 59 ft. to 20 ft. From 59 ft. to 20 ft. From 59 ft. to 20 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 20 ft. to Surface ft. From Surface ft. to Surface ft. From Surface ft. to Surface ft. From Surface ft. to Surface ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? 150'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	loess			
8	18	lms stringers w/intermittent clay			
18	23	1 ft. gray clay			
23	54	sand, clays w/ some intermit			
57	59	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 7-22-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 608 This Water Well Record was completed on (mo/day/year) 8-2-94 under the business name of Yellow Jacket Drilling by (signature) [Signature]