


1 LOCATION OF WATER WELL: Fraction SE 1/4 NW 1/4 SW 1/4 Section Number 2 Township Number T 14 S Range Number R 18 EW
 County: ELLIS

Distance and direction from nearest town or city street address of well if located within city?
1/4 mile east of intersection Canterbury and 9 Street Road, Hays, Ks. 67601

2 WATER WELL OWNER: ALLIED ASPHALT INC
 RR#, St. Address, Box #: Box 190 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Hays, Ks. Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 42.0 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 35.5 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 37.61 ft. below land surface measured on mo/day/yr 11/6/92
 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm
 Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm
 Bore Hole Diameter: 8.25 in. to 42 ft. and _____ in. to _____ ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW# 4
 Was a chemical/bacteriological sample submitted to Department? Yes _____ No X; If yes, mo/day/yr sample was submitted _____
 Water Well Disinfected? Yes _____ No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued _____ Clamped _____
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded _____
 7 Fiberglass Threaded X
 Blank casing diameter 2 in. to 27 ft. Dia _____ in. to _____ ft. Dia _____ in. to _____ ft.
 Casing height above land surface: 0 Flush mt., weight 703 lbs./ft. Wall thickness or gauge No. 154
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) _____
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) _____
 SCREEN-PERFORATED INTERVALS: From 27.0 ft. to 42.0 ft. From _____ ft. to _____ ft.
 From _____ ft. to _____ ft. From _____ ft. to _____ ft.
 GRAVEL PACK INTERVALS: From 25.0 ft. to 42.0 ft. From _____ ft. to _____ ft.
 From _____ ft. to _____ ft. From _____ ft. to _____ ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other _____
 Grout Intervals: From 2 ft. to 15 ft. From 25.0 ft. to _____ ft. From _____ ft. to _____ ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
OLD UST EXCAV.
 Direction from well? North east How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.4	ASPHALTIC PAVEMENT		36.5	
.4	2.5	FILL; CLAY, BLACK, M, FIRM, WITH GRAVEL	35.5	42.0	SAND, BE, Wet, LOOSE, Fine to Med grained, poorly graded
2.5	4.5	LOESS; SILT GR, M, SOFT (PEDIAN)			
4.5	6.5	CLAY, GR BR, M, SOFT, RUST			
6.5	10.5	CLAY, R BE, C + RUST STAINS, FAT (LOVELAND)	36.5	42.0	Silt, BE, Wet, Soft, Very Sandy, with some clay
10.5	16.0	TERRACE; SAND SEAM 2" THICK, M to C G, POORLY G., CLAY, GR BR, SM, FIRM, SILTY, C CONCRET			
16.0	19.5	Silt, LT BR, SM, Soft friable			
19.5	35.5	CLAY, LT BR, MOIST, FIRM, SILTY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/6/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 11/13/92 under the business name of Geotechnical Services Inc by (signature) David Wade Wallace

OFFICE USE ONLY T R EW SEC 1/4 1/4 1/4