


1 LOCATION OF WATER WELL: County: Ellis Fraction: SW 1/4 SE 1/4 NE 1/4 Section Number: 4 Township Number: T 14 S Range Number: R 18 E (EW)
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: RR#, St. Address, Box #: City of Hays Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Hays, Kansas 67601 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 1994
 Depth(s) Groundwater Encountered 1. 20.37 ft. 2. 35 ft. 3. 35 ft.
 WELL'S STATIC WATER LEVEL 20.37 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 20.37 ft. after 35 hours pumping 35 gpm
 Est. Yield 35 gpm: Well water was 20.37 ft. after 35 hours pumping 35 gpm
 Bore Hole Diameter: 20.37 in. to 35 ft., and 35 in. to 35 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well #5
 Was a chemical/bacteriological sample submitted to Department? Yes No X No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Threaded
 Blank casing diameter 2 in. to 35 ft., Dia. 20.37 in. to 35 ft., Dia. 35 in. to 35 ft.
 Casing height above land surface (Grade) Flush in., weight 35 lbs./ft. Wall thickness or gauge No. 010
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 35 ft., From 20.37 ft. to 35 ft., From 35 ft. to 35 ft.
 GRAVEL PACK INTERVALS: From 18 ft. to 35 ft., From 18 ft. to 35 ft., From 35 ft. to 35 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From Grade ft. to 16 ft., From 16 ft. to 18 ft., From 18 ft. to 18 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	Silty clay, brown, medium plasticity Stiff, dry trace root vesicles			
10	14	Clayey silt, Light brown, soft, moist, trace hairline fractures and root vesicles			
14	29	Silty clay, dark brown stiff, moist, trace hairline fractures			
29	34	Sand, brown fine to coarse grained, poorly sorted, wet			
34	35	Shale, dark gray, highly weathered filled fractures			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/29/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 468 This Water Well Record was completed on (mo/day/yr) November 25, 1991 under the business name of J & R Drilling Services, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC
1/4
1/4
1/4