			R WELL RECORD			1-1212		Range Number
LOCATION OF WA	TER WELL:	Fraction NW 1/4	SE ¼	SE 14	ection Number 3	Township Nur T 14	S R	18
stance and direction		own or city street			ty?			
000 Front Stree					***************************************			
WATER WELL OV						Board of Agricul	ture. Division of	Water Resources
#, St. Address, Box			Λ1			Application Num		1100000000
y, State, ZIP Code		a, Kansas 6/2	01	10.5	A 515V			2
LOCATE WELL'S L	ECTION BOX:	4 DEPTH OF CO	OMPLETED WELL	<del>9</del> 7,9	11. ELEV	2	# 3	
	_	Depth(s) Ground	water Encountered	0 1	's-2	L	molday/yr	11/19/98
	ł	WELL'S STATIC	WAIER LEVEL .		NA # 0	unace measured or for	hours numning	gpm
- NW	NE	Pum	o test data: VVell V	vater was	a. 	for	hours pumping	
		Est. Yield 174	exgpm: vve⊪v	waterwas		and	in to	
w	E		eter Ø In TO BE USED AS:					on well
,		1				9 Dewatering	12 Other	(Specify below)
- sw	- se	1 Domestic	4 Industrial	7 Lawn and	garden only	10 Monitoring well	Air S	parge Well
	- S <b>X</b>	2 Irrigation	4 industrial Mhacteriological sa	mole submitted	to Departmen	t? YesNo	; If yes, mo/d	ay/yr sample was
		submitted	w pacter lological se		Wa	ater Well Disinfected	d? Yes	No <b>√</b>
TYPE OF BLANK	CACING LICED:	<u> </u>	5 Wrought iron	8 Cor	crete tile	CASING JOI	VTS: Glued	Clamped
4	3 RMP (S		6 Asbestos-Cem		er (specify bek	ow)	Welded	
1 Steel	A ARS	,	7 Fiberglass					<b>√</b>
2) VC	4 ADS	in to 4°	7 ibergiass 75 ft Dia	ir	. to	ft., Dia	in.	to ft.
ank casing diametel	nnd surface		in weight		lbs	/ft. Wall thickness	orgauge No	Sch40
asing neight above it YPE OF SCREEN O	ANG SUNACE AD DEDECIDATIO	NI MATERIAI	. III., Weight	(7)F	PVC	10 Asbe	estos-cement	
1 Steel	3 Stainles		5 Fiberglass			11 Othe	r (specify)	
2 Brass	4 Galvaniz		6 Concrete tile	9 /		12 None	e used (open ho	le)
CREEN OR PERFO				auzed wrapped	l	8 Saw cut	11	None (open hole)
1 Continuous s		Viili slot		vire wrapped		9 Drilled holes		
2 Louvered shi		You nunched	7 Te	orch cut		10 Other (specify	)	
CREEN-PERFORAT		: From	. 47.5 ft. 1	to 49.5	ft., F	rom	ft. to	
ONEEN EN GIVE		From	ft. f	to		rom	ft. to	π.
GRAVEL PA	ACK INTERVALS	S: From	. <b>45.5</b> ft. t	to	ft., F	rom	ft. to	
		From		to				ft.
GROUT MATERIA	L: 1 Neat	t cement	2 Cement grout	(3)Be				
Frout Intervals: Fro	m 0	ft. to 34	ft., From	34	ft. to45.5	ft, From	ft.	to
What is the nearest s					10 Live	estock pens	14 Aband	oned water well
1 Septic tank		eral lines	7 Pit privy	y	(11) Fue	el storage	15 Oil well	/Gas well
2 Sewer lines	ss pool	8 Sewage lagoon		12 Fer	tilizer storage	16 Other (	specify below)	
3 Watertight sew		epage pit	o recayara			ecticide storage		
Direction from well?	West					any feet? 20		VAL 6
FROM TO		LITHOLOGIC	LOG	FROM	і то	PL	UGGING INTER	VALS
0 10	Clay, Brown	<u> </u>						
10 28	Clay, Orang	e Brown						
28 35	Clay, Gray/	Tan						
35 50	Sand, Gray/	Tan						
						AC 3 T- # 003023	22 Flush-	<u> </u>
							83133 , Flushmount	
							Pepsi-Cola Bottling Company - Remedial	
						GeoCore # 708, KI		
7 CONTRACTOR'S	OR LANDOWN	ER'S CERTIFICA	TION: This water w	well was (1) cor	nstructed, (2) re	econstructed, or (3)	plugged under	my jurisdiction
	on (moldaylyear	-)	10/19/98		and this	record is true to the	e best of my kno	wedge and belief.
and was completed t Kansas Water Well	Contractor's Lice	ense No	527	. This Water \	Nell Record wa	as completed on (mo	o/day/yr)/	11/20/98
under the business		GeoC	ore Services, In	ıc.	by (sign	nature)	h a ker	<b>5-</b> (
	<del>-</del>	2200				( Jal	人 " / "	