

1	LOCATION OF WATER WELL: Fraction	Section Number	Township Number	Range Number
County: Ellis	NE 1/4 NE 1/4 NE 1/4	25	T 14 S	R 18 EW

Distance and direction from nearest town or city street address of well if located within city?

863 280th Ave - Munjor KS

2	WATER WELL OWNER: Joe Englert	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	863 280th Ave	Application Number:
City, State, ZIP Code :	Munjor KS 67601	

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4	DEPTH OF COMPLETED WELL 40 ft. ELEVATION: upland
		Depth(s) Groundwater Encountered 1 20 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 7/21/03 Pump test data: Well water was 20 ft. after 2 hours pumping 15 gpm Est. Yield 15 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 7 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No			

5	TYPE OF BLANK CASING USED: 2	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded
Blank casing diameter 5 in. to 20 ft., Dia in. to ft., Dia in. to ft.				
Casing height above land surface 24 in., weight 2.29 lbs./ft. Wall thickness or gauge No. 26				
TYPE OF SCREEN OR PERFORATION MATERIAL: 7	7 PVC	10 Asbestos-Cement		
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)	11 Other (Specify)
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 8	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	9 Wire wrapped		
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ft.	
SCREEN-PERFORATED INTERVALS: From 40 ft. to 20 ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 18 ft. to 40 ft., From ft. to ft.				

6	GROUT MATERIAL: 3	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 18 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
Direction from well?			How many feet?		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	Topsoil and clay			
15	20	Clay and gumbo			
20	27	Sand			
27	40	Black shale			

7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/21/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 199 This Water Well Record was completed on (mo/day/yr) 8/1/03 under the business name of Karst Water Well Drilling & Service, Inc. by (signature) Mel Karst
---	---

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.