

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Ellis, Fraction: 1/4 NW 1/4 NW 1/4, Section Number: 3, Township Number: T 14 S, Range Number: R 18 E/W

Distance and direction from nearest town or city street address of well if located within city? Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: Grace Murphy, RR#, St. Address, Box #: 415 East 7th, City, State, ZIP Code: Hays, KS 67601

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N, S, W, E

4 DEPTH OF COMPLETED WELL: 45 ft. Depth(s) Groundwater Encountered (1) 24 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr. Pump test data: Well water was... hours pumping... gpm. Est. Yield 30 gpm: Well water was... hours pumping... gpm. WELL WATER TO BE USED AS: 1 Domestic, 3 Feedlot, 6 Oil field water supply, 8 Air conditioning, 11 Injection well, 2 Irrigation, 4 Industrial, 7 Domestic (lawn & garden), 9 Dewatering, 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr. Sample was submitted. Water well disinfected? Yes No

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued, Clamped, Welded, Threaded

Blank casing diameter 5 in. to 45 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 18 in., Weight 16.0 lbs./ft. Wall thickness or gauge No. SDR 36

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw Cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 45 ft. to 25 ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 45 ft. to 23 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well, 15 Oil well/gas well, 16 Other (specify below)

Direction from well? EAST How many feet? 30

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-2 TOP SOIL, 2-21 CLAY, 21-24 CLAY + SAND, 24-36 SAND, 36-41 CLAY, 41-45 SHALE

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/20/06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 478. This Water Well Record was completed on (mo/day/year) 10/20/06 under the business name of Hannersteel Water Well by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline, or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 422, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.