WATER	R WEL	L RECORD	Form W	WC-5	Division of Water	r Resources App. No).	
		OF WATER WELL:	Fraction		Section Number	Township No.	Range Number	
	ty: Ellis		NW 1/4 SE 1/4 SW		3	T 14 S	R 18 □E 🗗 W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here								
,					Latitude:			
East of 10th & Vine, Hays, KS					Elevation: (in decimal degrees)			
A WATER WEY YOWNER					Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Union Pacific Railroad RR#, Street Address, Box #: 1400 Douglas Street-Stop1030					Collection Method:			
G': G: GID G 1				☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
City, State, ZIP Code : Omaha, NE 68179					Est. Accuracy:			
3 LOCATE WELL 27.0								
i	WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 27.0 ft. ft. Depth(s) Groundwater Encountered (1).~20.0 ft. (2)							
SECT	N WELL'S STATIC WATER LEVEL. 20.82ft. below land surface measured on mo/day/yr							
	Pump test data: Well water wasft. after hours pumping							
_{NW}	EST. YIELDgpm. Well water wasft. afterhours pumpinggpm							
W	W							
^-	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SWSE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well MW1								
	Was a chemical/bacteriological sample submitted to Department? Yes No							
	S If yes, mo/day/yr sample was submitted							
1 mile Water well disinfected? ☐ Yes ✓ No								
5 TYPE OF CASING USED: Steel V PVC Other								
CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded ☑ Threaded								
Casing diameter .2								
Casing height above land surface5.64								
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other								
		est source of possible cont	amination:	l	16. 1011.,	. 140m	16. 60	
What is the nearest source of possible contamination: ☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ▼ Other (specify below)								
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedward ☐ Fertilizer storage ☐ Oil well/gas well ☐ Lust Site								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Lust Site ☐ Direction from well ☐ Distance from well Distance from well Distance from Well ☐ Distance from Well ☐ Distance fr								
FROM	TO	LITHOLOG		FROM			JGGING INTERVALS	
0	2.5	Sand & gravel						
2.5	7	Clay, silty						
7	7.5	Sand, gravel, medium	to fine					
7.5	11	Clay, silty		-				
11	17	Clay, sandy	, , , , , , , , , , , , , , , , , , , ,					
17	27	Sand, clayey, very fine	to medium			MW1		
						,		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .0.1/3.0/20.12 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 594 This Water Well Record was completed on mo/day/seat/93/06/2012								
under the business name ofCoranco Great Plains, Inc								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								