

1 LOCATION OF WATER WELL: County: SALINE Fraction: SW 1/4 SE 1/4 SW 1/4 Section Number: 19 Township Number: T 14 S Range Number: R 2 EW Distance and direction from nearest town or city street address of well if located within city? 1609 COURTNEY

2 WATER WELL OWNER: EARL DEBEER RR#, St. Address, Box #: 1609 COURTNEY City, State, ZIP Code: SALINA, KS. 67401 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: (Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants and an 'X' in the SW quadrant.) 4 DEPTH OF COMPLETED WELL: 52.5 ft. ELEVATION: 1230 Depth(s) Groundwater Encountered: 15.6 ft. WELL'S STATIC WATER LEVEL: 15.6 ft. below land surface measured on mo/day/yr: 5-23-96 Pump test data: Well water was 16.3 ft. after 1 hours pumping 20 gpm Est. Yield 75+ gpm: Well water was 16.3 ft. after 1 hours pumping 20 gpm Bore Hole Diameter: 5 in. to 5.3 ft., and 5 in. to 5.3 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) 10 Asbestos-cement Blank casing diameter: 5 in. to 44.5 ft., Dia. 44.5 in. to 52.5 ft., Dia. Casing height above land surface: 16 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot .035 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 44.5 ft. to 52.5 ft., From 52.5 ft. to 52.5 ft., GRAVEL PACK INTERVALS: From 35 ft. to 52.5 ft., From 52.5 ft. to 52.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 22 ft., From 22 ft. to 40 ft., From 40 ft. to 40 ft., From 40 ft. to 40 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? 40 WEST How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	FILL DIRT			
3	17	CLAY TAN SILTY			
17	53	SAND FINE TO MED. TAN			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-23-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 5-23-96 under the business name of PESTINGER PUMP SERVICE by (signature) Earl Debeer

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R EW SEC. 1/4 1/4 1/4