


1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 County: SALINE NE 1/4 NE 1/4 SW 1/4 19 T 14 S R 2 EW

Distance and direction from nearest town or city street address of well if located within city?
1033 EASTGATE DR.

2 WATER WELL OWNER: PAUL ADRIAN
 RR#, St. Address, Box # : 1033 EASTGATE DR. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : SALINA, KS. 67401 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION: 1230
 Depth(s) Groundwater Encountered 1. 14.3 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 14.3 ft. below land surface measured on mo/day/yr 7-24-96
 Pump test data: Well water was 14.9 ft. after 1 hours pumping 20 gpm
 Est. Yield 7.5+ gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 9 in. to 51 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded
 Blank casing diameter 5 in. to 45 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface 14 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot .035 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS: From 45 ft. to 50 ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From 40 ft. to 50 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 21 ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? NORTH How many feet? 40

FROM		TO		LITHOLOGIC LOG	FROM		TO		PLUGGING INTERVALS
0	4			FILL DIRT					
4	18			CLAY TAN SILTY					
18	50			SAND FINE TO COARSE					
50	51			SHALE GRAY HARD					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-24-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 7-24-96 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]

OFFICE USE ONLY
 T
 R
 EW
 SEC.
 1/4
 1/4
 1/4