| | * | | WA | TER WELL RECO | RD For | m WWC-5 | KSA 82 | | |
|---|---------------|-------------------|-------------------|-------------------------------|------------|-------------|---------------|---------------------------------|-----------------------------------|
| | ON OF WAT | | Fraction | | | | tion Number | | Range Number |
| County: S | aline | | NE NE | | | 1/4 | 31 | <u>T 14 S</u> | <u>R 2</u> KW |
| Distance a | nd direction | from nearest to | wn or city street | t address of well if | located wi | thin city? | | | |
| | | | | Ohio St., S | Salina, | KS | | | |
| | | NER: Smoks | | | | | | | |
| | | # : 645 E | | | | | | Board of Agricultu | ure, Division of Water Resource |
| | | <u>: Salir</u> | | | _ | | · | Application Numb | |
| 3 LOCATE | WELL'S LO | CATION WITH | 4 DEPTH OF | COMPLETED WE | ELL43 | | ft. ELEVA | ATION: | |
| → AN "X" | IN SECTION | I BOX: | | | | | | | ft. 3 |
| 7 [| XI I | | WELL'S STAT | IC WATER LEVE | | ft, b | elow land su | rface measured on mo/da | ıy/yr7/8/99 |
| 1 1 | Ì | | | | | | | | s pumping gpm |
| - | - NW | NE | | | | | | | s pumping gpm |
| ' | 1 1 | | | - | | | | | in. toft. |
| ĕ w ⊢ | | E | | R TO BE USED AS | | | rsupply | 8 Air conditioning | |
| - | i | i | 1 Domest | | | | | | 12 Other (Specify below) |
| 1 !- | - SW | SE | 2 Irrigatio | | | | | | ····· |
| | ! | ! ! | _ | | | | _ | | yes, mo/day/yr sample was sub |
| <u> </u> | <u>'</u> | | mitted | arbacteriologicar s | ample subi | inted to Di | | | s <u>y No</u> |
| EL TYPE O |)C OI ANK C | ASING USED: | Triitteu | 5 Wrought iro | • | 9 Const | | | Slued X Clamped |
| | | | ·D\ | = | | | | | • |
| 1 Ste なPV | | 3 RMP (S 4 ABS | ירון | 6 Asbestos-Co 7 Fiberglass | smem | | (specify belo | | Welded |
| | | | ·- •- 23 | | | | | | |
| | | | | | | | | | in. to ft. |
| _ | - | | | In., weight | 10,,1,0,, | | | | ge No 50.0 |
| • | | R PERFORATIO | | | | X PV | - | 10 Asbestos-c | |
| 1 Ste | - · <u>-</u> | 3 Stainles | | 5 Fiberglass | | | IP (SR) | | cify) |
| 2 Bra | | 4 Galvani: | | | | 9 AB | = | 12 None used | • |
| | | ATION OPENIN | | | Gauzed v | • • | | 8 Saw cut | 11 None (open hole) |
| | ntinuous slot | ~~ | Aill slot | | Wire wra | • | | 9 Drilled holes | |
| | uvered shutte | | Key punched | | Torch cut | | | | |
| SCREEN-F | PERFORATE | D INTERVALS: | | | | | | | ft. toft. |
| | | | | | | | | | ft. toft. |
| G | BRAVEL PAC | CK INTERVALS | | | | | | | ft. toft. |
| | | | From | | | | | | ft. to ft. |
| | MATERIAL | | cement | 2 Cement grou | | | | | |
| | | | | | | ft. | | | ft. to |
| | | urce of possible | | | | | | | 14 Abandoned water well |
| | ptic tank | | ral lines | 7 Pit pr | - | | | | 15 Oil well/Gas well |
| 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify bel | | | | | | | | 16 Other (specify below) | |
| | | er lines 6 Seep | page pit | 9 Feed | yard | | | - | |
| Direction for | | _North | | | | | | any feet? 50 | |
| FROM | TO | | LITHOLOGI | IC LOG | | FROM | то | PLUGGI | NG INTERVALS |
| _0 | 2 | Topsoil | | | | | | | |
| 2 | 18 | Gray_Cla | | | | <u> </u> | | | |
| 18 | 36 | _ Medium i | to_Coarse | Sand | | | | | |
| 36 | 42 | Coarse_9 | Sand with | large rock | | | | | |
| _42 | 43 | Shale | | | | | | | |
| | ļ <u>.</u> | | | | | | | | |
| | | | | | | | | | |
| | ļļ | | | | | | | | |
| | | | | | | | ļļ. | | |
| | <u> </u> | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | <u> </u> | | | | | | <u> </u> | | |
| | | | | | | | [<u>]</u> | | |
| | | | | | | | | | |
| 7 CONTE | RACTOR'S C | B LANDOWNE | R'S CERTIFICA | TION: This water | well was 7 | (i) constru | cted. (2) rec | onstructed, or (3) plugged | l under my jurisdiction and was |
| completed | on (mo/dav/s | vear) | 7/8/99 | me nate | | <u>.,</u> | and this reco | ord is true to the best of m | ly knowledge and belief. Kansas |
| | | | | | | | | on $(mo/day/y_f) \cdot . /7/20$ | |
| | | | | GATION, INC | | | = | | Vilum |
| | | oww. Priri | | | - | | عا الجانب وب | | |
| MICTOL | | | | • | | | | | three copies to Kansas Department |