

1 LOCATION OF WATER WELL: County: <u>Saline</u>	Fraction <u>NE 1/4 SW 1/4 SW 1/4</u>	Section Number <u>30</u>	Township Number T <u>14 S</u>	Range Number R <u>2 EW</u>
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1224 Nottingham

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code : <u>1224 Nottingham</u> <u>Saline, Kansas 67401</u>	Board of Agriculture, Division of Water Resources Application Number: <u>1234</u>
--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>46</u> ft. ELEVATION: <u>1234</u>
--	---

1 Mile

Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 16 ft.

WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 10-13-99

Pump test data: Well water was 16 ft. after 1 hours pumping 15 gpm

Est. Yield 30 gpm; Well water was 16 ft. after 1 hours pumping 15 gpm

Bore Hole Diameter 8 1/2 in. to 16 ft. and 5 1/2 in. to 46 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
<u>7 Lawn and garden only</u>				

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>5</u> in. to <u>36</u> ft. Dia			
Casing height above land surface <u>17</u> in., weight <u>160 LB</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From <u>36</u> ft. to <u>46</u> ft.		
GRAVEL PACK INTERVALS:	From <u>16</u> ft. to <u>46</u> ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>16</u> ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? <u>EAST</u>				How many feet? <u>27</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	2'	Compacted Fill Dirt			Waivered on depth of grout from Don Taylor
2'	6'	Top Soil & Hardpan			
6'	25'	FINE SAND & LIGHT BROWN CLAY mixed			
25'	30'	medium SAND & clay mixed			
30'	41'	medium SAND			
41'	42'	coarse River Rock			
42'	46'	coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-14-99</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>523</u> This Water Well Record was completed on (mo/day/yr) <u>10-14-99</u> under the business name of <u>M&D Well Service</u> by (signature) <u>Matthew Joubert</u>
--