


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 NW 1/4 Section Number 30 Township Number T 14 S Range Number R 2 W EW  
 County: SALINE

Distance and direction from nearest town or city street address of well if located within city?

#18 RED FOX LANE

2 WATER WELL OWNER: GREG BOYLE  
 RR#, St. Address, Box #: #18 RED FOX LANE Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: SALINA, KS. 67401 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 60'6" ft. ELEVATION: 1051  
 Depth(s) Groundwater Encountered: 1. 17 ft. 2. 16 ft. 3. 4-13-00 ft.  
 WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr 4-13-00  
 Pump test data: Well water was 16 ft. after 1 hours pumping 25 gpm  
 Est. Yield 75+ gpm: Well water was 16 ft. after 1 hours pumping 25 gpm  
 Bore Hole Diameter: 9 in. to 61 ft., and 61 in. to 61 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped. X  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded           
 2 PVC 4 ABS 7 Fiberglass          Threaded.           
 Blank casing diameter 5 in. to 50'6" ft., Dia          in. to          ft., Dia          in. to          ft.  
 Casing height above land surface 14 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 26  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)           
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot .025 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)          ft.  
 SCREEN-PERFORATED INTERVALS: From 50'6" ft. to 60'6" ft., From          ft. to          ft.  
 From 30 ft. to 60'6" ft., From          ft. to          ft.  
 GRAVEL PACK INTERVALS: From          ft. to          ft., From          ft. to          ft.  
 From          ft. to          ft., From          ft. to          ft.

6 GROUT MATERIAL: 1 Neat cement 0 2 Cement grout 30 3 Bentonite 4 Other           
 Grout Intervals: From          ft. to          ft., From          ft. to          ft., From          ft. to          ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? WEST How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	FILL DIRT			
2	5	TOP SOIL			
5	25	CLAY TAN SILTY			
25	61	SAND FINE TO COARSE TAN			
		WOOD ATX <del>35'</del> 35'			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-13-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 388 This Water Well Record was completed on (mo/day/yr) 4-13-00 under the business name of PESTINGER PUMP SERVICE by (signature) [Signature]