		WATE	R WELL RECORD	Form WWC	-5 KSA 82a-	1212		
1 LOCATION OF		Fraction	~~ 1.		ection Number	Township Number		
County: > 4		1554		E 1/4	24_	_ T 14 <b>&amp;</b> (	B)   R <b>3 2 6</b> (0)	
Distance and dire	<u> </u>	· · · ·	ddress of well if locate	d within city	?			
· · · · · · · · · · · · · · · · · · ·		aTRICE	I					
2 WATER WEL	LOWNER: R		HESON					
RR#, St. Address	s, Box # :9	41. Bec	grice			•	Iture, Division of Water Resources	
City, State, ZIP C			KANSAS			Application Nun		
LOCATE WEL	L'S LOCATION WITH		OMPLETED WELL	5.6	ft. ELEVA	TION:123	<i>1</i>	
AN "X" IN SEC	N BOX:	Depth(s) Ground	water Encountered 1	2	7 ft. 2		. ft. 3	
1	1	WELL'S STATIC	WATER LEVEL	2.7 ft	below land surf	ace measured on mo/o	day/yr 9-3-01	
	1 !	Pump	test data: Well water	er was . 🗩	_7.1/2_ft. at	ter lou	ırs pumping gpm	
NW	Nt	Est. Yield . 37	. gpm: Well water	erwas	ft. af	ter hou	urs pumping gpm	
	X	Bore Hole Diame	eter 🛪 🗷 🗷 in. to	30.		and5.1/2	in. to5/ft.	
* w	1 1		O BE USED AS:	5 Public w	ater supply	8 Air conditioning	11 Injection well	
-	1 1	1 Domestic	3 Feedlot	6_Oil field	water supply	9 Dewatering	12 Other (Specify below)	
sw	SE	2 Irrigation	4 Industrial					
1 1 :							If yes, mo/day/yr sample was sub-	
1 —		mitted	<b>3 7</b>			ter Well Disinfected? Y		
5 TYPE OF BLA	NK CASING USED:		5 Wrought iron	8 Cor	crete tile		Glued	
1 Steel	3 RMP (S	R)	6 Asbestos-Cement				Welded	
(2) VC	4 ABS_	•	7 Fiberglass			•	Threaded	
Blank casing diar		in to 41					in. to ft.	
							uge No. 50R26	
	EN OR PERFORATIO	. •	.m., woight	0		10 Asbestos		
1 Steel	3 Stainles		5 Fiberglass	_	RMP (SR)		pecify)	
2 Brass	4 Galvania		6 Concrete tile		ABS		ed (open hole)	
	RFORATION OPENIN			ed wrapped		8 Saw cut	11 None (open hole)	
1 Continuo		fill slot		wrapped	,	9 Drilled holes	Trans (open nois)	
2 Louvered		key punched	7 Torch	• •				
	PRATED INTERVALS:						. ft. toft.	
SONEEN-FENEC	MATED INTERVALS.						ft. to	
CRAVE	L DACK INTERVALE.	From		79		<u> </u>	ft. to	
GHAVE	L PACK INTERVALS:			••• ••.	ft., Fror			
C CDOUT MATE	RIAL: 1 Neat	From	ft. to 2 Cement grout	0.00			π.	
6 GROUT MATE	From Integral	cement	, the Frame	9 <sup>3 Be</sup>	ntonite 4	the Fram	ft. to ft.	
Grout Intervals:			π., From <del>≪</del>	<b>~</b> . <b>(</b> π	•			
	est source of possible		7 84				14 Abandoned water well	
1 Septic tank 4 Lateral lines			7 Pit privy			11 Fuel storage 15 Oil well/Gas well		
2 Sewer lin		•	8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)		
	t sewer lines 6 Seep		9 Feedyard			ticide storage	<del></del> · · · · · · · · · · · · · · · · · ·	
Direction from we		The	100	T EDOM	How mar		SING INTERVALS	
FROM TO		LITHOLOGIC		FROM	то	12000	INTO INTERVALS	
91 2	MIRV		scied 5:	4	-			
7 2	Light	Brow	Sh Clay					
	and	FINC.	) HND'II	LLX.				
27/ 2/	nt mali							
271 30	mean	im JAI	up + clay	<u> </u>		The second secon		
	mixe	L						
	1 40 1		1 1 1 7 mi					
30'5	medi	Um ,5	ANDA					
	91	AveL						
	V							
					1,			
7 CONTRACTO	R'S OR LANDOWNE	R'S CERTIFICATI	ON: This water well w	as (Thi cons	tructed, (2) reco	nstructed, or (3) pluga	ed under my jurisdiction and was	
completed on (m	o/day/year) 9-3	-01					my knowledge and belief. Kansas	
	actor's License No	523	This Water V	Vell Record	was completed	on (mo/dav/vr), 9	-4-01	
under the busine	44		( Service		by (signat		- Subse	
							p three copies to Kansas Department	
						VNER and retain one for your		