


1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 SE 1/4 Section Number 30 Township Number T 14 S Range Number R 2 W
 County: SALINE

Distance and direction from nearest town or city street address of well if located within city?
2267 Redhawk

2 WATER WELL OWNER: Jim DAVIS
 RR#, St. Address, Box #: 2267 Redhawk Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Salina, KS 67401 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: 1232
 Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 15 ft.
 WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 5-4-02
 Pump test data: Well water was 18 ft. after 1/2 hours pumping 15 gpm
 Est. Yield 30 gpm; Well water was 18 ft. after 1/2 hours pumping 15 gpm
 Bore Hole Diameter 8 1/2 in. to 23 in. and 5 1/2 in. to 48 in.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 38 in. Dia. in. to 38 in. Dia. in. to 38 in. Dia. in. to 38 in. Dia.
 Casing height above land surface 16 in., weight 160 LB lbs./ft. Wall thickness or gauge No. 50R26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 38 ft. to 48 ft., From 38 ft. to 48 ft., From 38 ft. to 48 ft., From 38 ft. to 48 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 48 ft., From 23 ft. to 48 ft., From 23 ft. to 48 ft., From 23 ft. to 48 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 23 ft., From 0 ft. to 23 ft., From 0 ft. to 23 ft., From 0 ft. to 23 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? WEST How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	2'	Fill dirt			
2'	4'	Compacted top soil			
4'	23'	Brown clay			
23'	26'	Grey clay			
26'	32'	Medium sand			
32'	34'	Grey clay (dark)			
34'	48'	Coarse sand + gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-9-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 523 This Water Well Record was completed on (mo/day/yr) 5-9-02 under the business name of M+D Well Service by (signature) Matthew Tenhip

OFFICE USE ONLY
T
R
EW
SEC.