


1 LOCATION OF WATER WELL: County: SALINE Fraction: NE 1/4 SW 1/4 NW 1/4 Section Number: 19 Township Number: T 14 S Range Number: R 2 EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: 1204 Fredrick Wanda L. Doherty  
 RR#, St. Address, Box #: 1204 Fredrick  
 City, State, ZIP Code: SALINA, KS 67401  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 51 ft. ELEVATION: 1226  
 Depth(s) Groundwater Encountered 1. 28 ft. 2. 28 ft. 3. 28 ft.  
 WELL'S STATIC WATER LEVEL: 28 ft. below land surface measured on mo/day/yr 10-12-02  
 Pump test data: Well water was 28 ft. after 1/2 hours pumping 15 gpm  
 Est. Yield 40 gpm; Well water was 28 ft. after 5 1/2 hours pumping 51 gpm  
 Bore Hole Diameter: 8 1/2 in. to 28 ft., and 5 1/2 in. to 51 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  
2 PVC 4 ABS 7 Fiberglass Threaded  
 Blank casing diameter 5 in. to 4 1/2 ft., Dia. 5 in. to 4 1/2 ft., Dia. 5 in. to 4 1/2 ft.  
 Casing height above land surface 16 in., weight 160 LB lbs./ft. Wall thickness or gauge No. SDR 26  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 2 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 2 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 4 1/2 ft. to 51 ft., From 4 1/2 ft. to 51 ft., From 4 1/2 ft. to 51 ft.  
 GRAVEL PACK INTERVALS: From 29 ft. to 51 ft., From 29 ft. to 51 ft., From 29 ft. to 51 ft.  
 From 22 ft. to 28 ft., From 22 ft. to 28 ft., From 22 ft. to 28 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 28 ft. to 29 ft., From 0 ft. to 22 ft., From 0 ft. to 22 ft., From 0 ft. to 22 ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? West & South How many feet? 12 ft & 15 ft

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	4'	SILL DIRT			
4'	5'	TOP SOIL			
5'	21'	BROWN CLAY			
21'	29'	LIGHT SAND & CLAY MIX BROWN			
29'	51'	MEDIUM TO COARSE SAND & GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-13-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 523 This Water Well Record was completed on (mo/day/yr) 10-13-02 under the business name of M&D Well Service by (signature) Matthew Loukup

OFFICE USE ONLY  
T  
R  
EW  
SEC.  
1/4  
1/4  
1/4