

1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 SW 1/4 Section Number 19 Township Number T 14 S Range Number R 21 E/W

County: SALINE Distance and direction from nearest town or city street address of well if located within city? 1259 EASTGATE COURT

2 WATER WELL OWNER: DON FINK RR#, St. Address, Box #: 1259 EASTGATE COURT Board of Agriculture, Division of Water Resources City, State, ZIP Code: SALINA, KS. 67401 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-acre section with an 'X' in the SW corner.] 4 DEPTH OF COMPLETED WELL: 52 ft. ELEVATION: 1230

Depth(s) Groundwater Encountered 21 ft. 21 ft. 2 ft. 3 ft. 5-09-03 ft.

WELL'S STATIC WATER LEVEL: 21 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 23 ft. after 1 hour pumping 20 gpm

Est. Yield: 7.5+ gpm Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded

2 PVC 4 ABS 7 Fiberglass 9 Other (specify below)

Blank casing diameter: 5 in. to 47 ft. Dia 160 in. to 26 ft. Dia

Casing height above land surface: 14 in., weight lbs./ft. Wall thickness or gauge No. SD# 26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)

2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot .025 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) ft.

7 Torch cut

SCREEN-PERFORATED INTERVALS: From 47 ft. to 52 ft. From ft. to ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 22 ft. to 52 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 22 ft., From ft. to ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? NORTH How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	FILL DIRT			
3	10	CLAY BROWN SILTY			
10	22	SILT TAN			
22	52	SAND FINE TO MED. TAN			
52		SHALE GRAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-09-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 388 This Water Well Record was completed on (mo/day/yr) 5-9-03 under the business name of PESTINGER PUMP SERVICE by (signature) Paul Pestinger