


ID No.

1) LOCATION OF WATER WELL: County: SALINE		Fraction NW ¼ NW ¼ NW ¼	Section Number 31	Township Number T 14 S	Range Number R 2W E/W
Distance and direction from nearest town or city street address of well if located within city? 2403 AMB ASSADOR					
2) WATER WELL OWNER: KATX AL THISSEN RR#, St. Address, Box # : 2403 AMBASSDOR City, State, ZIP Code : SALINA, KS. 67401 Board of Agriculture, Division of Water Resources Application Number:					
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"></div>		4) DEPTH OF COMPLETED WELL 54 ft. ELEVATION: 1234 Depth(s) Groundwater Encountered 1 19 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 7-24-03 Pump test data: Well water was 22 ft. after 1 hours pumping 25 gpm Est. Yield 754 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes X No			
5) TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 49 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 16 in., weight 169 lbs./ft. Wall thickness or gauge No. SDR 26 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot .025 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 49 ft. to 54 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 22 ft. to 54 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 22 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? NORTHWEST How many feet? 40 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 4 FILL DIRT 4 18 CLAY BROWN SILTY 18 54 SAND FINE TO MED. TAN					
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-24-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 388 This Water Well Record was completed on (mo/day/yr) 7-28-03 under the business name of PESTINGER PUMP SERVICE by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-298-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					