

1 LOCATION OF WATER WELL: County: <u>SALINA</u>	Fraction <u>SN 1/4 E 1/4 S 1/4</u>	Section Number <u>17</u>	Township Number <u>T 14 S</u>	Range Number <u>R 2W E/W</u>
--	---------------------------------------	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
124 EASTMOOR DR.

2 WATER WELL OWNER: GREG DIXBY
RR#, St. Address, Box # : 124 EASTMOOR DR.
City, State, ZIP Code : SALINA, KS. 67401
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	-- NW --	-- NE --	E
		X	
	-- SW --	-- SE --	
	S		

4 DEPTH OF COMPLETED WELL 49 1/2 ft. ELEVATION: 1217

Depth(s) Groundwater Encountered 18 ft. 2 18 ft. 3 24-04 ft.
WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 3-24-04
Pump test data: Well water was 37 ft. after 1 hours pumping 25 gpm
Est. Yield 30 gpm: Well water was 37 ft. after 1 hours pumping 25 gpm
WELL WATER TO BE USED AS:
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u> </u>
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u> </u>
		7 Fiberglass		Threaded <u> </u>

Blank casing diameter 5 in. to 39 1/2 ft., Dia 160 in. to 30R 26 ft., Dia in. to ft.
Casing height above land surface 20 in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify) <u> </u>
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot <u>0.25</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify) <u> </u>	

SCREEN-PERFORATED INTERVALS: From 39 1/2 ft. to 49 1/2 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 21 ft. to 49 1/2 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 21 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
<u>3 Watertight sewer lines</u>	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? NORTH How many feet? 22

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	FILL DIRT			
3	13	CLAY BROWN			
13	15	DRIFT BROWN			
15	36	CLAY BROWN FINE			
36	49	SAND FINE TAN WITH DRIFT MIXED BROWN			
49	50	SHALE			
					(DRILLED 10" HOLE AND PACKED WITH 8-12 SAND)

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-24-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 388 This Water Well Record was completed on (mo/day/yr) 3-24-04 under the business name of PASTINGER PLUMB SERVICE by (signature) [Signature]