			TER WELL RE	CORD	For	m WWC	C-5 K	SA 82a-	-1212 ID N	lo			····	
1 LOCATIO	Fraction					Section Number			wnship Nu	umber	Range Number			
County: Sa				4 SE		NW	1/4		31	T	14	S	R 2	X /W
		rom nearest tow	•				ted withir	n city?						
	<u>limits</u> WELLOWN	, Teton NER: Jona	St. Sal as Hecke		Ks									
RR#, St. Add	dress. Box		6 Repub		ŀr.					В	oard of Ad	riculture. D	ivision of Wate	r Resource
City, State, Z	IP Code	: Sali	ina. Ks	. 6	740	1				Α	pplication	Number:		
3 LOCATE V	VELL'S LO	CATION WITH	4 DEPTH OF	COMPL	ETED	WELL .	52		ft. ELEVA	TION:				
	SECTION I		 Depth(s) Gro	undwate	r Enco	untered	1		f	t. 2		ft. 3		ft.
	<u> </u>		WELL'S STA	TIC WAT	ER LE	√EL	.1.0	ft. bel	ow land surface	ce measu	red on mo	/day/yr		
	; 1			ump tes	t data:	Well w	vater was		ft.	after		hours pu	umping	gpn
NW NE Est. Yield					0-50 gpm: Well water was						umping	gpn		
1 Domes					ic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							elow)		
w	I I	E	2 Irrigatio	n 4	Indust	rial				10 Monit	toring well			
	sw	- SE	14/		! !! .		-1	:44! 4 -	D t +0	V	No. V	. 16	- /	
	carbacte	eriologic	ai sam	pie subm	iitea to	o Department? Yes NoX; If yes, mo/day/yrs sample was sub Water Well Disinfected? Yes x No								
	1	1	mitted						***	C.C. 11011	21011110010	G. 100	Λ	
F TVD= 0:	S	ACINIC LICES									011.0	NITO T:	. V -:	
TYPE OF BLANK CASING USED:					rought i	ron Comon	. 8	Concr	ete tile (specify belov		SING JOI		dX Clamı	
1 Steel 3 RMP (SR) ★ PVC 4 ABS					6 Asbestos-Cement 7 Fiberglass				(specify below				ed aded	
	diameter	5	in. to		_									
		nd surface												
		PERFORATIO			,			7 X P\				estos-Cem		
1 Steel 3 Stainless Steel					5 Fiberglass			8 RMP (SR))	
2 Brass		4 Galvaniz	ed Steel	6 Cd	oncrete	tile		9 AE	38		12 Nor	ne used (op	en hole)	
SCREEN OF	R PERFOR	ATION OPENIN	IGS ARE:			5 G	iuazed w	rapped		8 Sav			11 None (ope	n hole)
	nuous slot		ill slot				/ire wrap	ped			led holes			
2 Louve	ered shutter	4 K	ey punched				orch cut				` ' '	,		
SCREEN-PE	ERFORATE	D INTERVALS:												
	DV/EI DV	Y INTERVALO	From	20	•••••	ft. to		 ว	ft., From	١	•••••	ft. to		ft
l G	HAVEL FAC	CK INTERVALS:												

<u></u>	MATERIA		cement			t grout								
1		· 0			ft., Fr	om		ft.	to	ft., F	rom		ft. to	ft
1		irce of possible		:						tock pens			bandoned wate	
1		4 Later			7 Pit privy			11 Fuel st				15 O	il well/Gas well	l
2 Sewe		5 Cess	•		8 Sewage I			•			_	16 O	ther (specify be	elow)
Direction from well?					9 Feedyard									• • • • • • • • • • • • • • • • • • • •
Direction fro	10.100	7				How mai	ny feet?							
FROM	ТО		LITHOLOG	iiC LOG			F	ROM	ТО		PLU	IGGING IN	IERVALS	
0	3	Topsoi											11 A. J. A. W.	
3	23	Clay,												
23	49		medium			se								
49	52	Shale,	gray											

			444											
												•••		
7 CONTRA														A-A-A-A-
- CONTINA	CTOR'S O	R LANDOWNE	R'S CERTIFIC	ATION:	This wa	ater we	ll wa (1)	constr	ucted, (2) rec	onstructed	d, or (3) p	lugged und	ler my jurisdicti	on and wa
completed or	(mo/day/y	ear)		.0.4	•••••	This 141			and this re	cord is tru	e to the be	est of my kn	owledge and be	elief. Kansa
under the bus	siness nam	Licence No		•		THIS VV	ater well	necord	was complete	eu on (mo. (signature	/day/yr)	8/2/0	4 -	••••••