

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Saline</u>	<u>SW</u> 1/4 <u>SW</u> 1/4 <u>SE</u> 1/4	<u>30</u>	T <u>14</u> S	R <u>2</u> <u>E</u> <u>W</u>

Distance and direction from nearest town or city street address of well if located within city?
2336 River Trail

2 WATER WELL OWNER: <u>Stacy Wireman</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>2336 River Trail</u>	Application Number:
City, State, ZIP Code : <u>Salina, KS</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>44.4</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered: 1 18.1 ft. 2 31.8/1.5 ft.

WELL'S STATIC WATER LEVEL 18.1 ft. below land surface measured on mo/day/yr 3/18/05

Pump test data: Well water was 50 gpm. Well water was 50 gpm. hours pumping 50 gpm.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	<u>7</u> Domestic (lawn & garden)	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒ No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>✓</u> Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
<u>2 PVC</u>	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			

Blank casing diameter 5 in. to 34.4 ft., Dia 18 in. to 16.0 ft.

Casing height above land surface 18 in., weight 16.0 lbs./ft. Wall thickness or gauge No. 16.0

TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-Cement	11 Other (Specify)	12 None used (open hole)
1 Steel	8 RMP (SR)		
2 Brass	9 ABS		
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	<u>3</u> Mill slot	5 Guazed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 34.4 ft. to 44.4 ft., From 44.4 ft. to 50 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 50 ft., From 50 ft. to 50 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>0</u> ft. to <u>30</u> ft., From <u>30</u> ft. to <u>50</u> ft.				

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
<u>3</u> Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? E. How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>22</u>	<u>Clay</u>			
<u>22</u>	<u>30</u>	<u>Sand, f-m</u>			
<u>30</u>	<u>40</u>	<u>Sand, m-c</u>			
<u>40</u>	<u>48</u>	<u>Sand, f</u>			
<u>48</u>	<u>50</u>	<u>Shale</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, <u>(2)</u> reconstructed, or <u>(3)</u> plugged under my jurisdiction and was completed on (mo/day/year) <u>3/18/05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>527</u> This Water Well Record was completed on (mo/day/yr) <u>3/17/05</u> under the business name of <u>GeoCore Inc</u> by (signature) <u>Dale A. Bell</u>

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.