

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Saline

Location listed as:

Section-Township-Range: 19-2-14W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): SW SE SW

Location changed to:

19-14-2W

SW SE SW

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: County maps, record location information

initials: mf date: 9-20-06

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726


to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 SW 1/4 Section Number 19 Township Number T 2 S Range Number R 14 E/W
 County: Saline

Distance and direction from nearest town or city street address of well if located within city?
1505 E. Claylin

2 WATER WELL OWNER: Wayne Pruitt
 RR#, St. Address, Box #: 1505 E. Claylin Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Saline KS Application Number: 1230

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 48 1/2 ft. ELEVATION: 1230
 Depth(s) Groundwater Encountered 1. 21 ft. 2. 21 ft. 3. 21 ft.
 WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr 8-26-06
 Pump test data: Well water was 21 ft. after 1/2 hours pumping 15 gpm
 Est. Yield 30 gpm. Well water was 21 ft. after 1/2 hours pumping 15 gpm
 Bore Hole Diameter 8 1/2 in. to 21 ft., and 5 1/2 in. to 48 1/2 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 38 1/2 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 18 in., weight 160.16 lbs./ft. Wall thickness or gauge No. SDR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 Continuous slot Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 38 1/2 ft. to 48 1/2 ft., From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 21 ft. to 48 1/2 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 21 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? South How many feet? 11

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	8'	LT BR Clay			
8'	21'	LT BR Clay + FINE SAND MIX			
21'	30'	Med SAND + grey clay mixed			
30'	48 1/2'	Medium to coarse SAND + GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-26-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 523 This Water Well Record was completed on (mo/day/yr) 8-26-06 under the business name of M&D Well Service by (signature) Matthew Joubert