

1 LOCATION OF WATER WELL: Fraction NW 1/4 JW 1/4 NE 1/4 Section Number 31 Township Number T 14 S Range Number R 2 E

Distance and direction from nearest town or city street address of well if located within city?  
2419 Calcutta

2 WATER WELL OWNER: Jennifer Motter  
RR#, St. Address, Box #: 2419 Calcutta  
City, State, ZIP Code: Salina, KS 67401  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
N  
NW NE  
W E  
SW SE  
S

4 DEPTH OF COMPLETED WELL 45 ft. ELEVATION: 1231  
Depth(s) Groundwater Encountered 1 16 ft. 2 ft. 3 ft.  
WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 3-29-08  
Pump test data: Well water was 16 ft. after 1 hours pumping 15 gpm  
Est. Yield 35 gpm: Well water was 16 ft. after 1 hours pumping 15 gpm  
WELL WATER TO BE USED AS:  
5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X; if yes, mo/day/yr sample was submitted Water Well Disinfected? Yes

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
7 Fiberglass Threaded  
Blank casing diameter 5 in. to 36 ft., Dia 36 in. to ft., Dia  
Casing height above land surface 16 in., weight 160 LB lbs./ft. Wall thickness or gauge No. SDR 26  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement  
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)  
12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
7 Torch cut 10 Other (specify) ft.  
SCREEN-PERFORATED INTERVALS: From 36' ft. to 45' ft., From ft. to ft.  
GRAVEL PACK INTERVALS: From 16' ft. to 45' ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout intervals: From 0' ft. to 16' ft., From ft. to ft. to ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? West How many feet? 45'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	3'	fill dirt + topsoil			Talked to Richard Harper on 3-31-08 about waiver on grout depth 9:30 AM
3'	8'	Light Brown clay			
8'	16'	Light Br clay + fine SAND mixed			
16'	30'	fine SAND			
30'	45'	medium to coarse SAND AND GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-31-08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 523 This Water Well Record was completed on (mo/day/yr) 4-2-08 under the business name of MTD Well Service by (signature) Matthew Soukup