WATER WELL R				ion of Water		
Original Record				rces App. No.		Well ID
1 LOCATION OF W		action		on Number	Township Numb	
		145'L 148E 14NA	-	30	T 14 S	R
2 WELL OWNER: L						(if unknown, distance and
Business: PIERC	Y HOMES		•	arest town or into	ersection): If at owner	r's address, check here:
	ox 3173		# a	/ / >	_	\bigcap
City: SALI		P: 67401	50	ω	LDOAT	CIECLE
3 LOCATE WELL	4 DEPTH OF COMPL		25			
WITH "X" IN				1		(decimal degrees)
SECTION BOX:	Depth(s) Groundwater Enco 2) ft. 3)					(decimal degrees)
N	WELL'S STATIC WATER				WGS 84 □ NAI	
	below land surface, mea	sured on (mo-day-yr)	04-22-14		r <u>Latitude/Longitude</u> (unit make/model:	<u>.</u>
NW NE	above land surface, mea	sured on (mo-day-yr)			(WAAS enabled?	
	Pump test data: Well water				Survey Topogra	
W	after hours pun		m			
SW SE		was ft.				
1 1 1 1	after hours pun		m	6 Elevation	n· ft	. Ground Level TOC
S	Estimated Yield:gg Bore Hole Diameter:gg	pm in to	t and			GPS Topographic Map
mile		in. to f				or o D ropographme map
7 WELL WATER TO		111. 10				
1. Domestic:		upply: well ID		10. □ Oil Fi	eld Water Supply: 16	ease
☐ Household		ow many wells?			e: well ID	
■ Lawn & Garden		rge: well ID			☐ Uncased ☐ €	
Livestock		rell ID		12. Geothern	nal: how many bores	s?
2. Irrigation		mediation: well ID			d Loop Horizont	
3. Feedlot	☐ Air Sparge	☐ Soil Vapor Extr	raction			ischarge
4. Industrial	☐ Recovery	☐ Injection		13. ∐ Other	(specity):	
	iological sample submitted	d to KDHE? 🗌 Yes	s 🔽 No 🛚 l	If yes, date sa	mple was submitte	ed:
Water well disinfected?	X Yes □ No	,				
8 TYPE OF CASING	USED: 🗆 Steel 🗷 PVC 🗆] Other	CASING	G JOINTS: 🟲	K Glued □ Clamped	d ☐ Welded ☐ Threaded
8 TYPE OF CASING USED: Steel PVC Other						
Casing height above land surface in. Weight AD. lbs./ft. Wall thickness or gauge No. S. D. Lab.						
Casing height above land	surface in.	Weight!. (2.1)	to lbs./ft.	ft., Diamete Wall thicknes	r in. to ss or gauge No. S.b	ft. L∴∂6.
Casing height above land TYPE OF SCREEN OF	surface ! .(in. R PERFORATION MATER	Weight !. (2. (2. IAL:	to lbs./ft.	Wall thicknes	s or gauge No. J.A	L ∴d6
Casing height above land TYPE OF SCREEN OF ☐ Steel ☐ Stain	surface	Weight .1.60.D IAL: s ⊠ PVC	lbs./ft.	Wall thicknes	s or gauge No. J.A	ft. L-∂6.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv	surface	Weight .1.60.D IAL: s ⊠ PVC	lbs./ft.	Wall thicknes	s or gauge No. J.A	L ∴d6
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR	surface	Weight	lbs./ft.	Wall thicknes	s or gauge No. ふん	L-d6.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	Weight	lbs./ft. I (open hole) n Cut □ Dri	Wall thicknes ☐ Other ((Specify)	L-db.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	Weight	lbs./ft. I (open hole) n Cut □ Dri	Wall thicknes ☐ Other ((Specify)	L-db.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	Weight	lbs./ft. I (open hole) n Cut □ Dri	Wall thicknes ☐ Other ((Specify)	L-db.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE 9 GROUT MATERIA	surface	Weight	I (open hole) Cut	Wall thicknes Other (Iled Holes ne (Open Hole ft. to ner	Specify)	ft. to ft ft.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From	surface	Weight	I (open hole) Cut	Wall thicknes Other (Iled Holes ne (Open Hole ft. to ner	Specify)	ft. to ft ft.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible	surface	Weight	I (open hole) Cut	Wall thicknes Other of the control	(Specify)	ft. to ft.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank	surface	Weight	I (open hole) Cut	Wall thicknes Other of the control	Other (Specify) Other (Specify)	## Proof Pro
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) ft., From ft. to	## Proof Pro
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Company	Other (Specify) Other (Specify) the first of the fir	ft. to ft.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Company	Other (Specify) Other (Specify) the first of the fir	ft. to ft.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line	surface	Weight	I (open hole) I Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft ft ft. cide Storage oned Water Well ell/Gas Well
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft.
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft ft ft. cide Storage oned Water Well ell/Gas Well
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft ft ft. cide Storage oned Water Well ell/Gas Well
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft ft ft. cide Storage oned Water Well ell/Gas Well
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft ft ft. cide Storage oned Water Well ell/Gas Well
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft ft ft. cide Storage oned Water Well ell/Gas Well
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft ft ft. cide Storage oned Water Well ell/Gas Well
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO	surface	Weight	I (open hole) Cut	Wall thicknes Other of the Country	Other (Specify) Other (Specify) other (Specify) ft., From ft., From Insection Abandore Oil We	ft. to ft ft ft. cide Storage oned Water Well ell/Gas Well
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 17 57 57 57. 5	surface	Weight	I (open hole) I (ope	Wall thicknes Other (Other (Iled Holes ne (Open Hole ft. to ner rt., From ivestock Pens uel Storage ertilizer Storage TO LI	Specify)	ft. to ft ft ft ft. cide Storage oned Water Well ell/Gas Well r PLUGGING INTERVALS
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 17 57 57 57. 5	surface	Weight	I (open hole) I (ope	Wall thicknes Other (Other (Iled Holes ne (Open Hole ft. to ner rt., From ivestock Pens uel Storage ertilizer Storage TO LI	Specify)	ft. to ft ft ft ft. cide Storage oned Water Well ell/Gas Well r PLUGGING INTERVALS
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 17 57 57 57. 5	surface	Weight	I (open hole) I (ope	Wall thicknes Other (Other (Iled Holes ne (Open Hole ft. to ner rt., From ivestock Pens uel Storage ertilizer Storage TO LI	Specify)	ft. to ft ft ft ft. cide Storage oned Water Well ell/Gas Well r PLUGGING INTERVALS
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well? 10 FROM TO 17 57 57 57. 5	surface	Weight	I (open hole) I (ope	Wall thicknes Other (Other (Iled Holes ne (Open Hole ft. to ner rt., From ivestock Pens uel Storage ertilizer Storage TO LI	Specify)	ft. to ft ft ft ft. cide Storage oned Water Well ell/Gas Well r PLUGGING INTERVALS
Casing height above land TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 17 57 57 57. 5	surface	Weight	I (open hole) I (open hole) I Cut	Wall thicknes Other of the Country	Specify)	methods. fl. to

KSA 82a-1212

Visit us at http://www.kdheks.gov/waterwell/index.html

Revised 9/10/2012