

1 LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number
County: <u>Saline</u>		<u>NW 1/4 SW 1/4 SW 1/4</u>	<u>29</u>	<u>T 14 S</u>	<u>R 2W E/W</u>
Distance and direction from nearest town or city? <u>1 Mi. E. Salina</u>			Street address of well if located within city?		


2 WATER WELL OWNER: Harry E. Cline
 RR#, St. Address, Box #: Rt. 3
 City, State, ZIP Code: Salina Kans 67401
 Board of Agriculture, Division of Water Resources
 Application Number:

3 DEPTH OF COMPLETED WELL: 44.5 ft. Bore Hole Diameter: 6 in. to 44.5 ft. and in. to ft.
 Well Water to be used as:
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 7 Lawn and garden only 10 Observation well
 Well's static water level: 2.1 ft. below land surface measured on Sept. month 8 day 1980 year
 Pump Test Data: Well water was ND ft. after 1/2 hours pumping 30 gpm
 Est. Yield 40 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing dia: 4 in. to 41.5 ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface: 1.2 in. weight lbs./ft. Wall thickness or gauge No. SDR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 Screen or Perforation Openings Are:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 Screen-Perforation Dia: 7 in. to 44.5 ft. Dia in. to ft. Dia in. to ft.
 Screen-Perforated Intervals: From 41.5 ft. to 44.5 ft. From ft. to ft. From ft. to ft.
 Gravel Pack Intervals: From 3.5 ft. to 44.5 ft. From ft. to ft. From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grouted Intervals: From 3 ft. to 1.3 ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination: Open field
 1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well
 3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)
 13 Watertight sewer lines
 Direction from well: How many feet? Water Well Disinfected? Yes X No
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, date sample was submitted month day year Pump Installed? Yes No X
 If Yes: Pump Manufacturer's name Model No. HP Volts
 Depth of Pump Intake ft. Pumps Capacity rated at gal./min.
 Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on Sept month 8 day 1980 year
 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 126
 This Water Well Record was completed on Sept month 10 day 1980 year under the business name of Hydraulic Drilling Co by (signature) O. J. Fent

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
0 20 Clay & silt, gray-brown
20 27 Sand, fine, silty
27 38 Clay, gray
38 44.5 Gravel & sand, fine

ELEVATION:
 Depth(s) Groundwater Encountered 1. 2.1 ft. 2. 3.8 ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

14

R

8

EED

SEC

29

NW 1/4 SW 1/4 SW 1/4