

1 LOCATION OF WATER WELL: SALINE County: SALINE Fraction SE 1/4 SW 1/4 SW 1/4 Section Number 30 Township Number T 14 S Range Number R 2 EW

Distance and direction from nearest town or city street address of well if located within city?
1316 SEQUOIA DR.

2 WATER WELL OWNER: LOUIS BOLING
RR#, St. Address, Box #: 1316 SEQUOIA DR.
City, State, ZIP Code: SALINA, KS. 67401
Board of Agriculture, Division of Water Resources
Application Number: 1231

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is marked in the SW quadrant. A vertical scale on the left indicates 1 Mile. The grid is labeled with N, S, E, W directions.]

4 DEPTH OF COMPLETED WELL: 46 ft. ELEVATION: 1231

Depth(s) Groundwater Encountered 1. 18 ft. 2. . ft. 3. . ft.

WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 9-17-90

Pump test data: Well water was 19 ft. after 1 hours pumping 30 gpm

Est. Yield 75+ gpm: Well water was . ft. after . hours pumping . gpm

Bore Hole Diameter: 9 in. to 46 ft., and . in. to . ft.

WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes . No X If yes, mo/day/yr sample was submitted . Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 5 in. to 36 ft. Dia. in. to . ft. Dia. in. to . ft.

Casing height above land surface 15 in. weight 160 lbs./ft. Wall thickness or gauge No. SDR 26

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) .
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot .035 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 36 ft. to 46 ft. From . ft. to . ft.

GRAVEL PACK INTERVALS: From 20 ft. to 46 ft. From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 0 ft. to 20 ft. From . ft. to . ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? SOUTH How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TOP SOIL			
1	18	SANDY LOAM			
18	36	SAND			
36	37	CLAY			
37	46	MED. SAND & GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-17-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 388 This Water Well Record was completed on (mo/day/yr) 9-17-90 under the business name of PESTINGER PUMP SERVICE by (signature) Paul Pestinger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC
1/4
1/4
1/4