LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 SW 19 19 T 1/4 S R 2	fater Resource fit. 4. 30 gpr gpr fy below) ample was su
WATER WELL OWNER: DWATN LIFE R#, St. Address, Box #: 1513 COURTNEY WATER WELL OWNER: DWATN LIFE R#, St. Address, Box #: 1513 COURTNEY Board of Agriculture, Division of W. Application Number: LOCATE WELL'S LOCATION WITH A DEPTH OF COMPLETED WELL 52. ft. ELEVATION: 1230. Depth(s) Groundwater Encountered 1. 14. ft. 2. ft. 3. WELL'S STATIC WATER LEVEL 14. ft. below land surface measured on mor/day/yr. 8-19-9 Pump test data: Well water was 17. ft. after 1. hours pumping Board of Agriculture, Division of W. Application Number: LOCATE WELL'S LOCATION WITH A DEPTH OF COMPLETED WELL 52. ft. ELEVATION: 1230. Depth(s) Groundwater Encountered 1. 14. ft. 2. ft. 2. ft. 3. WELL'S STATIC WATER LEVEL 14. ft. below land surface measured on mor/day/yr. 8-19-9 Pump test data: Well water was 17. ft. after 1. hours pumping Boare Hole Diameter 9. in to 52. ft., and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Speci 2 Irrigation 4 Industrial 7. Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. X. If yes, mor/day/yr s mitted Water Well Disinfected? Yes X No TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X. Cla Well water was 17. ft. Dia in. to ft. Dia in. to saing height above land surface 18 in., weight 160 lbs://t. Wall thickness or gauge No. SDR 2 YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Other (specify)	fater Resource fit. 4. 30 gpr gpr fy below) ample was su
WATER WELL OWNER: DWAIN LIPE Board of Agriculture, Division of Ways, State, ZIP Code SALTNA, KS, 67401 Application Number: No. 200 Application Num	
WATER WELL OWNER: DWAIN LITE ##, St. Address, Box # : 1513 COURTNEY ##, Application Number: ##, Application	
Application Number: 1230. Depth(s) Groundwater Encountered 1. 14	
Application Number: Application Number: Application Number: Application Number: Application Number: Application Number: 1230. Depth(s) Groundwater Encountered 1. 14 ft. 2. ft. 3. WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr .8-19-9 Pump test data: Well water was 17. ft. after 1 hours pumping Est. Yield 100. gpm: Well water was 17. ft. after hours pumping Bore Hole Diameter 9. in to 52 ft. and in to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specical Price of BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X. Classing diameter 5 in to 47 ft. Dia in to 50 ft. Dia in to 50 sing height above land surface 18 in, weight 160 lbs:/ft. Wall thickness or gauge No. SDR .2 PE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Other (specify)	ft. 30 gpr gpr f l fy below) ample was su
DEPTH OF COMPLETED WELL 52. ft. ELEVATION: 1230. Depth(s) Groundwater Encountered 1. 14. ft. 2. ft. 3. WELL'S STATIC WATER LEVEL 14. ft. below land surface measured on mo/day/yr 8-19-9 Pump test data: Well water was 17. ft. after 1 hours pumping. Bore Hole Diameter 9. in. to 52. ft. and in. to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specient 1) Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X. Classing diameter 5 in. to 47 ft. Dia in. to ft. Dia in. to sing height above land surface. 18 in., weight 160 PEPTH OF COMPLETED WELL 52. ft. and in. to ft. Dia in. to sing height above land surface 1 in. to 47 ft. Dia in. to 52. ft. after hours pumping 12 Other (Specify below) Well water supply 9 Dewatering 12 Other (Specify below) Water Well Disinfected? Yes X No X if yes, mo/day/yr s in. to 47 ft. Dia in. to ft. Dia in. to sing height above land surface. 18 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 2 PE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 11 Other (specify)	ft. 30 gpr gpr f l fy below) ample was su
WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 8-19-9 Pump test data: Well water was 17 ft. after 1 hours pumping Est. Yield 100 gpm: Well water was ft. after hours pumping Bore Hole Diameter 9 in to 52 ft., and in to WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes. No X if yes, mo/day/yr s mitted Water Well Disinfected? Yes X No TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X. Cla 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) PURC 4 ABS 7 Fiberglass Threaded. Threaded.	4
Est. Yield 100 gpm: Well water was ft. after hours pumping Bore Hole Diameter 9 in to 52 ft., and in to well water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Special Section of the process of	gpi f l fy below) ample was su
Est. Yield 100. gpm: Well water was ft. after hours pumping land to both the pumping set of the pumping set	fy below)ample was su
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Speci- 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. X if yes, mo/day/yr s witted Water Well Disinfected? Yes X No. TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Cla 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded. ank casing diameter 5 in. to 47 ft., Dia in. to ft., Dia in. to sing height above land surface. 18 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 2 PE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	fy below)ample was su
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Speci- 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No. X; If yes, mo/day/yr s Water Well Disinfected? Yes X No. TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Cla 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded. ank casing diameter 5 in. to 47 ft., Dia in. to ft., Dia in. to Sing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. SDR 2 (PE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 11 Other (specify)	fy below)ample was su
2 Irrigation 4 Industrial 7 I awn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes	ample was su
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr s witted water Well Disinfected? Yes X No TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Class 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	ample was su
S mitted Water Well Disinfected? Yes X No TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Cla 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded. ank casing diameter 5 in to 47 ft., Dia in to ft., Dia in to asing height above land surface 18 in , weight 160 lbs./ft. Wall thickness or gauge No. SDR 2 YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	mped
TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X. Clarification 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	mped
2 PVC 4 ABS 7 Fiberglass Threaded. ank casing diameter 5 in to 47 ft., Dia in to ft., Dia in to sing height above land surface 18 in, weight 160 lbs./ft. Wall thickness or gauge No. SDR 2 PE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
ank casing diameter 5 in to 47 ft., Dia in to ft., Dia in to sing height above land surface 18 in, weight 160 lbs./ft. Wall thickness or gauge No. SDR 2 (PE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
asing height above land surface	
YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	Þ
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (c	pen hole)
1 Continuous slot 3 Mill slot •035 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
CREEN-PERFORATED INTERVALS: From	
From ft. to ft., From ft. to	
GRAVEL PACK INTERVALS: From	
From ft. to ft., From ft. to	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
rout Intervals: From	
hat is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned w. 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas w.	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	Delow)
irection from well? WEST How many feet? 50	
ROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
θ 2 FILLDIRT	
2 18 CLAY TAN SILTY	
18 52 SAND FINE TO COARSE	
52 SHALE GRAY	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed or (3) plugged under my indied	ction and we
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisd moleted on (molday/year) 8-19-94	
mpleted on (mo/day/year) 8-19-94 and this record is true to the best of my/knowledge and	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisd mpleted on (mo/day/year) 8-19-94 and this record is true to the best of my/knowledge and ater Well Contractor's License No. 388 This Water Well Record was completed on (ma/day/yr) 8/19-94 der the business name of PESTINCER PUMP SERVICE by (signature)	