

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <b>SALINE</b>		<b>SE 1/4 SW 1/4 SW 1/4</b>	<b>30</b>	<b>T 14 S</b>	<b>R 28 E</b>
Distance and direction from nearest town or city street address of well if located within city? <b>2329 Salimar</b>					
2 WATER WELL OWNER: <b>DOUG OIL PLANT</b>					
RR#, St. Address, Box # : <b>2329 Salimar</b>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <b>SALINA, KANSAS 67401</b>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <b>46 1/2</b> ft. ELEVATION: <b>1231</b>			
		Depth(s) Groundwater Encountered <b>16</b> ft. 2. <b>16</b> ft. 3. <b>16</b> ft.			
		WELL'S STATIC WATER LEVEL <b>16</b> ft. below land surface measured on mo/day/yr <b>3-12-95</b>			
		Pump test data: Well water was <b>16 1/2</b> ft. after <b>15</b> hours pumping <b>15</b> gpm			
		Est. Yield <b>30</b> gpm: Well water was <b>16 1/2</b> ft. after <b>15</b> hours pumping <b>15</b> gpm			
		Bore Hole Diameter <b>8 1/2</b> in. to <b>17</b> ft., and <b>5 1/2</b> in. to <b>46 1/2</b> ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial <b>7</b> Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes <b>X</b> No <b>X</b> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <b>X</b> No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued <b>X</b> Clamped
<b>2</b> PVC		4 ABS	7 Fiberglass		Welded
					Threaded
Blank casing diameter <b>5</b> in. to <b>36 1/2</b> ft., Dia. <b>16</b> in. to <b>160 LB</b> lbs./ft. Wall thickness or gauge No. <b>SDR26</b>					
Casing height above land surface <b>16</b> in., weight <b>160 LB</b>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	<b>8</b> Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <b>36 1/2</b> ft. to <b>46 1/2</b> ft., From <b>17</b> ft. to <b>46 1/2</b> ft.					
GRAVEL PACK INTERVALS: From <b>17</b> ft. to <b>46 1/2</b> ft., From <b>17</b> ft. to <b>46 1/2</b> ft.					
6 GROUT MATERIAL: <b>1</b> Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <b>0</b> ft. to <b>17</b> ft., From <b>17</b> ft. to <b>46 1/2</b> ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
<b>3</b> Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <b>North &amp; East</b>		How many feet? <b>20'</b>		<b>20' &amp; 21'</b>	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<b>0'</b>	<b>6'</b>	<b>Compacted dirt &amp; silt</b>			
<b>6'</b>	<b>13'</b>	<b>Light Brown clay &amp; fine SAND mixed</b>			
<b>13'</b>	<b>21'</b>	<b>FINE SAND</b>			
<b>21'</b>	<b>29'</b>	<b>Medium SAND</b>			
<b>29'</b>	<b>30'</b>	<b>Dark grey clay</b>			
<b>30'</b>	<b>46 1/2'</b>	<b>Coarse to medium SAND AND gravel</b>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <b>1</b> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) <b>3-14-95</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>523</b> This Water Well Record was completed on (mo/day/yr) <b>3-14-95</b> under the business name of <b>M + D Well Service</b> by (signature) <b>Matthew Loukup</b>					